

# Statistica™ 13.2

## Silent Installer Instructions

# Products supported

Single-User and Workstation installs can be deployed silently. Server installs cannot be deployed silently.

The following Statistica products can be deployed silently:

- Single-User (32-bit and 64-bit) [Domain-Based Registration (DBR) is NOT supported]
- Concurrent Network License Workstation (32-bit and 64-bit)
- Concurrent Network License with Borrowing Workstation (32-bit and 64-bit)
- Statistica Enterprise Workstation (32-bit and 64-bit)

Note that Workstation installs with Domain-Based Registration (DBR) can be deployed silently.

# Operating system

- Windows Vista
- Windows 7
- Windows 8
- Windows Server 2003
- Windows Server 2008
- Windows Server 2008 R2
- Windows Server 2012

# Prerequisites

Internet Explorer 7 or later must be installed prior to using the Statistica MSI Installer.

# Syntax

Syntax for the Statistica MSI Installer includes the user interface, install properties, and an optional log file.

## User interface

You can control the amount of User Interface you see during the install process by using various switches. UI options include:

`/qn` No user interface (completely silent mode). This can also be specified as `/quiet`

- /qr Reduced user interface with a modal dialog box displayed for successful registration
- /qf Full user interface. This is the default if no user interface options are specified
- /passive Passive user interface with a progress bar to indicate that an installation is in progress

**NOTE:** For Vista and later operating systems: If installing to Windows Vista, you will see an elevation prompt when the install execute sequence begins. When running the installer in completely silent mode (/qn), you must start the install from an elevated command prompt; otherwise the installer will fail because completely silent installs will not prompt for elevation.

## Install properties

The following properties can be defined for installs:

Required Installation Codes (Single-User only):

SERIALNUMBER	Statistica-supplied Serial Number
PRODUCTKEY	Statistica-supplied Product Key
INSTALLCODE	Statistica-supplied Install Code

Required User Registration Information (Single-User only):

REG_FIRSTNAME	User First Name
REG_LASTNAME	User Last Name
REG_COMPANY	Company Name
REG_TITLE	User Title
REG_ADDRESS	Address
REG_CITY	City
REG_COUNTRY	Country

Uses the full country name and is case sensitive.  
(e.g., 'Germany' or 'United States')

REG_STATE	State
	This is the two-letter state/province abbreviations for the United States and Canada (e.g., 'TX' or 'ON', for Texas and Ontario). For all other countries, the full name is used. This property is also case sensitive. For the United States, Canada, France, and Australia, the state property must match one of the states from the drop-down box, or it will be reset. For all other countries, the state property can be any value.
REG_ZIP	Zip/Postal Code
REG_PHONE	Phone Number
REG_EMAIL	Email Address First Field (needed for product registration)
REG_EMAIL2	Email Address Second Field (must match the first email address field)

Optional installation path (Single-User or Workstation):

INSTALLDIR	Installation directory; if not supplied, defaults to C:\Program Files\Dell\Statistica 12
------------	---

Certain installations may want to install to a non-default path such as E:\Statistica 12

Optional shortcut flag (Single-User or Workstation):

B_DESKTOP_SHORTCUT	When set to 1, a shortcut to Statistica is created on the "All Users" desktop When set to 0, no shortcut is created
--------------------	--

Optional multimedia flag (Single-User or Workstation):

**INSTALLMULTIMEDIA** When set to 1, multimedia overviews (over 300 MB) are installed  
When set to 0, overviews are not installed

Optional license manager shortcut flag (Workstation only):

**INSTALLLICENSEMANAGER** When set to 1, Concurrent License Manager shortcut to the Start Menu is enabled  
When set to 0, shortcut is not enabled

Optional server flag (Concurrent Network License with Borrowing Workstation only):

**NETWORKINSTALL** When set to 1, files are installed to run from the server  
When set to 0, files are copied locally

Optional legacy tools flag (Enterprise Local Workstation only)

**INSTALLLEGACYTOOLS** When set to 1, Legacy Enterprise Tools (Historical Data Edit and Gage Setup) are installed on a local Enterprise workstation  
When set to 0, tools are not installed

## Option log file

For detailed debugging, you can enable MSI logging with the `/l* <logfile>` switch:  
`msiexec /i "D:\Statistica 12.0.1033.0.msi" /qn /l* c:\install.log`

## Launching through setup.exe

Launching the msi directly through msiexec will not check for (or install) any prerequisites that may be missing. Thus, the prerequisites should be preinstalled, or the silent installation should be launched through setup.exe. Use the `/s` argument to run the setup.exe in silent mode and the `/v` argument to pass in all msi properties. MSI properties containing spaces should use quotes escaped by a backslash.

```
"D:\setup.exe" /s /v"SERIALNUMBER=xxx PRODUCTKEY=xxx INSTALLCODE=xxx REG_COUNTRY=\"United States\" /qn"
```

## Installing via the command line

Following are example Single-User and Workstation silent installs.

Note that strings that include embedded spaces must be enclosed by double-quotes.

### Single user

The Single-User silent install utilizes the user registration (`REG_*` properties) and key (`PRODUCTKEY`, `INSTALLCODE`, and `SERIALNUMBER`) properties. When performing a Single-User silent install, the installer will attempt to contact the registration server to register your software electronically during the install. If automatic registration is not possible, a temporary 14-day license file will be created instead.

This example uses the `/qn` switch (a completely silent install) and specifies a desktop shortcut. Note that address information containing spaces are enclosed by double-quotes.

```
msiexec /i "D:\Statistica 12.0.1133.0.msi" /qn B_DESKTOP_SHORTCUT=1 PRODUCTKEY=XXXXXXXXX  
INSTALLCODE=XXXXXXXX SERIALNUMBER=XXXXXXXX REG_FIRSTNAME=John REG_LASTNAME=Doe
```

```
REG_TITLE=Statistician REG_COMPANY="ACME Inc." REG_ADDRESS="2300 E 14th St" REG_CITY=Tulsa  
REG_STATE=OK REG_COUNTRY="United States" REG_ZIP=74104 REG_PHONE=918-749-1119  
REG_EMAIL=user@company.com REG_EMAIL2=user@company.com
```

The same command launching through setup.exe to include pre-requisite installation:

```
"D:\setup.exe" /s /v"/qn B_DESKTOP_SHORTCUT=1 PRODUCTKEY=XXXXXXXXX INSTALLCODE=XXXXXXXX  
SERIALNUMBER=XXXXXXXXX REG_FIRSTNAME=John REG_LASTNAME=Doe REG_TITLE=Statistician  
REG_COMPANY="ACME Inc.\" REG_ADDRESS="2300 E 14th St" REG_CITY=Tulsa REG_STATE=OK  
REG_COUNTRY="United States\" REG_ZIP=74104 REG_PHONE=918-749-1119  
REG_EMAIL=user@company.com REG_EMAIL2=user@company.com
```

## Workstation

The Workstation silent installer excludes user registration and key information, which are part of the server install.

You can map a drive to the \Statistica 12\ folder on the server:

```
msiexec /i "D:\Workstation Installer 32\Statistica 12.0.1133.0.msi" /qn
```

or

```
"D:\Workstation Installer 32\setup.exe" /s /v"/qn"
```

Alternatively, you can use the UNC path to the \Statistica 12\Workstation Installer 32\ folder on the server:

```
msiexec /i "\\ServerName\Statistica 12\Workstation Installer 32\Statistica 12.0.1133.0.msi" /qn
```

or

```
"\\ServerName\Statistica 12\Workstation Installer 32\setup.exe" /s /v"/qn"
```

Note that you cannot map a drive directly to the Workstation Installer 32/ 64 directory.

## Uninstalling via the command line

Here is an example Single-User silent uninstall.

Note that strings that include embedded spaces must be enclosed by double-quotes.

A previous installation can be uninstalled by using the following command-line:

```
msiexec /uninstall "D:\Statistica 12.0.1133.0.msi"
```

The parameter can either specify the original MSI file or the Product Code, which is a code associated with each release of Statistica. This code can be read from the registry by finding the Statistica Add/Remove program file entry from the registry key:

```
HKEY_LOCAL_MACHINE\Software\Microsoft\Windows\CurrentVersion\Uninstall
```

For example, here is a registry location of the Add/Remove program entry for Statistica:

```
KEY_LOCAL_MACHINE\Software\Microsoft\Windows\CurrentVersion\Uninstall\{909b6a0e-bd44-5336-7cd4-63a08cfb9a6d}, where {909b6a0e-bd44-5336-7cd4-63a08cfb9a6d} is the Product Code.
```

The syntax to uninstall that version using the Produce Code is:

```
msiexec /uninstall {909b6a0e-bd44-5336-7cd4-63a08cfb9a6d}
```

# About Statistica

Statistica listens to customers and delivers worldwide innovative technology, business solutions and services they trust and value. For more information, visit <https://support.software.dell.com/statistica/>.

## Contacting Statistica

Technical Support:  
[Online Support](#)

Product Questions and Sales:  
(800) 306-9329

Email:  
[info@software.dell.com](mailto:info@software.dell.com)

## Technical support resources

Technical support is available to customers who have purchased Statistica software with a valid maintenance contract and to customers who have trial versions. To access the Support Portal, go to <https://support.software.dell.com/statistica/>.

The Support Portal provides self-help tools you can use to solve problems quickly and independently, 24 hours a day, 365 days a year. In addition, the portal provides direct access to product support engineers through an online Service Request system.

The site enables you to:

- Create, update, and manage Service Requests (cases)
- View Knowledge Base articles
- Obtain product notifications
- Download software. For trial software, go to [Trial Downloads](#).
- View how-to videos
- Engage in community discussions
- Chat with a support engineer