

# Spotlight® on Oracle 10.6

## Release Notes

April 2018

These release notes provide information about the Spotlight® on Oracle release.

Topics:

[About this release](#)

[New Features](#)

[Resolved Issues and Enhancements](#)

[Deprecated Features](#)

[Known Issues](#)

[System Requirements](#)

[Product Licensing](#)

[Getting Started](#)

[Globalization](#)

[About us](#)

## About this release

Spotlight is a powerful diagnostic and resolution tool for Oracle databases. Its unique user interface provides you with an intuitive, visual representation of the activity on your database. Graphical flows illustrate the rate at which data is moving between database components. Icons display the value of key statistics and metrics.

## Spotlight on Oracle

Spotlight on Oracle is used to diagnose the performance of Oracle instances running on individual host machines. It also includes the following products:

- **Predictive Diagnostics.** Use this to predict the future performance for individual SQL statements, bottlenecks, and database resources on the Oracle database.
- **Spotlight on Unix and Spotlight on Windows.** Launch the appropriate O/S Spotlight automatically when Spotlight connects to an Oracle database.
- **Spotlight on MySQL.** Diagnose the performance of MySQL instances.
- When delivered as part of the Toad® DBA Suite for Oracle, Spotlight incorporates **SQL Optimizer for Oracle**. SQL Optimizer offers a fully automated approach to maximizing SQL performance. It eliminates the manual, time-intensive process of ensuring that SQL code is performing as fast as possible.

## Spotlight on Oracle RAC

**Spotlight on Oracle RAC** requires additional licensing. It enables the diagnosis of Oracle databases on multiple host machines under the Real Application Clusters (RAC) architecture and additionally may include monitoring of Exadata systems depending on the license purchased.

- Spotlight on Oracle 10.6 is a minor release,
- with no new functionality. See [Resolved issues](#).

## New Features

### Spotlight on Oracle 10.6

Spotlight on Oracle 10.6 is a maintenance release with no new functionality.

### Spotlight on Oracle 10.5

Spotlight on Oracle 10.5 is a maintenance release with no new functionality.

### Spotlight on Oracle 10.4

Spotlight on Oracle 10.4 is a maintenance release with no new functionality.

### Spotlight on Oracle 10.3.3

Spotlight on Oracle 10.3.3 is a maintenance release with no new functionality.

### Spotlight on Oracle 10.3.2

Spotlight on Oracle 10.3.2 is a maintenance release with no new functionality.

### Spotlight on Oracle 10.3.1

**Windows 10:** Windows 10 is a supported platform for the installation of Spotlight on Oracle and the Spotlight Diagnostic Server, and for monitoring.

### Spotlight on Oracle 10.3

**In-Memory Diagnostics:** Spotlight now provides diagnostic information for In-Memory databases in Oracle and Oracle RAC. What is the cost to the database of enabling In-Memory? Has the right amount of memory been allocated to the In-Memory column store? To what extent is I/O being consumed by In-Memory activities? Drilldown further by segments, SQL, statistics and sessions.

# Resolved Issues and Enhancements

The following is a list of issues addressed and enhancements implemented in this release.

Area	Resolved Issue	Defect ID
Monitoring	Corrected a problem with the Configuration and Memory drilldown, Memory tab when monitoring Oracle 12.2.	SOO-2675
	Corrected a problem with the Top Sessions drilldown where for DB time the grid displays zero for some connections.	SOO-2668
Cloud Connect	Fixed an issue where for Spotlight Diagnostic Server setup to update to the cloud, Oracle alarms did not display on the Spotlight cloud website and Spotlight APPs.	DS-1284

The following is a list of issues addressed and enhancements implemented in 10.5.

Area	Resolved Issue	Defect ID
Top Sessions drilldown	Enhancement - Use the Filter icon to show/hide background type sessions.	SOO-2593
Time to Failure alarm	Enhancement - Now able to calculate mountpoint space by running a series of scripts. For more information, see <a href="https://support.quest.com/spotlight-on-oracle/kb/215461">https://support.quest.com/spotlight-on-oracle/kb/215461</a> .	SOO-2583
I/O   summary drilldown	Corrected erroneous negative values to 0 when the "Consumer Group" category is selected.	SOO-1681
Hungarian Locale	Corrected source of Exception error when creating an Oracle RAC connection in the Hungarian locale.	SOO-2298
Live Connections display	Corrected a problem where sometimes the selected Live Connection is no longer listed on the left pane connection display.	SOO-1634

The following is a list of issues addressed and enhancements implemented in 10.4.

Area	Resolved Issue	Defect ID
Installation	Dependency on .Net 3.5 is now removed. Spotlight on Oracle is now dependent on .Net 4.0 or above.	SOO-2421
Monitoring	Spotlight on Oracle supports monitoring of Oracle 12.2.	SOO-2605
Alarms	Corrected a problem where the Array Fetch Alarms were raised when the Spotlight User was the only connected user to the database.	SOO-2592
	On adding an alarm action to send an email when the alarm is raised, the content of the email has been cleaned of special characters making it much easier to read.	SOO-2618
Creating a connection	Corrected a problem where click "View information about objects installed and privileges required by Spotlight " when creating an Oracle RAC connection with a new user resulted in an unexpected error.	SOO-2560
General	Corrected problem causing unexpected error with message: Assertion failure	SOO-

Area	Resolved Issue	Defect ID
	(E:\Jenkins\jobs\SoO Nightly Build - from GIT\workspace\Spotlight\Source\MDK\components\SpotlightGraphics.pas, line 348)	2610

The following is a list of issues addressed and enhancements implemented in 10.3.3.

Area	Resolved Issue	Defect ID
Browse History	Corrected the source of an unexpected error (Interface not supported) when using the History Browser.	2557
Spotlight user creation script	References to the QUEST_LUCY_COLLECTOR package have been removed from the Spotlight user creation script for Oracle 11gR2 and above.	2569
	Removed code involving the SYS objects (SYS.EXECUTE_IMMEDIATE and SYS.BUILD_XVIEW) from the Spotlight user creation script for Oracle 11gR2 and above.	2568

The following is a list of issues addressed and enhancements implemented in 10.3.2.

Area	Resolved Issue	Defect ID
Spotlight Cloud	Corrected a problem on sign in to Spotlight Cloud from the Spotlight on Oracle client through a proxy server.	2272
Tablespace Utilization drilldown	Corrected the source of an unexpected error ("Range check error") on the Disk Storage   Tablespace utilization drilldown.	2481
General	Corrected the source of unexpected errors ("Integer overflow" Source 02041D9D) when using Spotlight functionality using a periodic timer like the slideshow.	2488
Monitoring Unix Connections	Corrected a problem where the memory value display was incorrect on the Spotlight on Unix home page for some Unix connections. This issue was related to Linux bug <a href="https://bugzilla.redhat.com/show_bug.cgi?id=1246379">https://bugzilla.redhat.com/show_bug.cgi?id=1246379</a>	2516
Top Sessions	Corrected Overflow error in Top session drilldown.	2510
Predictive Diagnostics	Corrected a problem where Predictive Diagnostics charts displayed no data.	2517
Spotlight charts	Corrected a problem with the zoom functionality in Spotlight charts.	2524

The following is a list of issues addressed and enhancements implemented in 10.3.1.

Area	Resolved Issue	Defect ID
Monitoring UNIX connections	Fixed a problem where no data was displayed for Disk Reads and Disk Writes when monitoring a Unix connection, AIX 7.1 server.	2433
Monitoring Oracle connections	Fixed a problem on the Tuning   Memory Management drilldown page where Total Oracle Memory failed to accept a 6 digit number.	2434
	Fixed a problem on the Configuration & Memory   Buffer Cache drilldown page where no data was displayed in the buffer cache details grid when a non-default	2437

Area	Resolved Issue	Defect ID
	pool was selected.	
General	Resolved "Integer Overview" issue.	2430

The following is a list of issues addressed and enhancements implemented in 10.3.

Area	Resolved Issue	Defect ID
Slideshow	You can now configure the Slideshow to remain active through mouse or keyboard activity.	2300
Licensing	Spotlight on Oracle can now accept licensing per monitored instance.	2323
Spotlight Web Publisher	The Spotlight Web Publisher is now merged into the Spotlight Diagnostic Server. In previous releases of Spotlight on Oracle the Spotlight Diagnostic Server and Web Publisher were both required to use Spotlight Mobile. Now only the Spotlight Diagnostic Server is required. On upgrade to Spotlight on Oracle 10.3 the Spotlight Web Publisher will be removed automatically.	2355
Unexpected Area	Fixed a problem where an Unexpected Error   Integer Overflow occurred on resizing a drilldown window.	2296
Monitoring Oracle connections	On the Alert Log drilldown fixed error ORA 01426: numeric overflow. The Log viewer can open files up to 2Gb in size.	2309
Top Sessions	Fixed the source of the following error on the Top Sessions drilldown: "Duplicates not allowed in table TopSessionsWithoutEvent".	2354
Monitoring Oracle Data Guard	Fixed issues connecting to a Data Guard Standby database in environments with fast connections.	2326
Monitoring Exadata	Fixed a problem where Spotlight is incorrectly derived the cell port number from the subnet mask.	2290
Monitoring Unix	Fixed a problem where Spotlight could not connect to Red Hat 7.	2291

## Deprecated Features

Oracle 10g R1 is no longer supported.

Windows Vista is no longer a supported operating system.

Windows Server 2008 R1 is no longer a supported operating system.

## Known Issues

The following is a list of issues known to exist at the time of this release.

Feature	Known Issue	Defect ID
General	<b>Spotlight data not displayed when overhead settings are restored to default values:</b> In some cases, restoring Overhead Management settings on a Spotlight component may prevent the display of Spotlight data in one or more drilldown pages. To view the data, disconnect the original Spotlight connection and then reconnect.	
	<b>Queued Spotlight queries will complete despite changes to Overhead Management settings:</b> When you use Spotlight's Overhead control to reduce or halt the collection of data from a connection, any existing queries that have been queued for execution will complete as if started under the previous overhead setting.	
Installation issues	<b>Brackets not permitted in installation path names:</b> Prior to Oracle 11g, the Oracle client does not support an installation path for Spotlight that contains the brackets "(" and ")". For example: C:\Program Files (x86)\...	
	<b>Tip:</b> For 64-bit operating systems we recommend not installing Spotlight on Oracle (Windows 32) in "c:\Program Files" since Windows re-directs this back to "C:\Program Files (x86)".	
	<b>Installing for multi-user access.</b> If Spotlight is installed for use by multiple users of a system, the additional users must be local administrators.	
Upgrade issues	When upgrading to Spotlight on Oracle 10.3.2 history data will be reset. If you would like to keep history between upgrades then you can change the folder spotlight stores history to, through Spotlight Options   storage->History Location.	

## Known Issues - Monitoring Oracle Databases

Feature	Known Issue	Defect ID
Connections	After connecting once with an Oracle 11g or Oracle 12c client, if you change the Oracle home to use a different client, the next time you connect you may see the error <b>Entry Point Not Found...</b>	2226
	From a Spotlight on Oracle connection where the Oracle database is installed on a Windows operating system, from drilldown <b>Operating System   OS Processes</b> right click on an Oracle process and select <b>Top Sessions</b> to open the Top Sessions drilldown - results in error: <b>Unable to file Oracle session for this process.</b>	2197
	<p><b>Limitations with automatic reconnection to Oracle systems:</b></p> <ul style="list-style-type: none"> <li>• <b>Connection lost during initial connection:</b> Spotlight will not reconnect if the connection is lost while Spotlight is initializing its connection.</li> <li>• <b>Connection lost while viewing alert log:</b> Spotlight will report a number of errors if the disconnection and reconnection occurs while the Alert Log drilldown is open.</li> </ul> <p><b>Spotlight on Oracle connections:</b> Spotlight on Oracle RAC automatically creates Spotlight on Oracle connections for each instance in the cluster. If, for example, you name your Oracle RAC connection "<b>My cluster</b>", and it has two instances with instance names of "<b>CL1</b>" and "<b>CL2</b>", then two Spotlight on Oracle connections named "<b>My cluster CL1</b>" and "<b>My cluster CL2</b>" will be</p>	

Feature	Known Issue	Defect ID
	<p>created automatically when you first connect Spotlight to the cluster. If you already have Spotlight on Oracle connections with those names, the connection details will be overwritten by Spotlight on Oracle RAC. If you subsequently delete the Oracle RAC "<b>My cluster</b>" connection, you will need to delete the associated Spotlight on Oracle connections manually.</p>	
	<p><b>Avoid simultaneous REXEC and SSH connections:</b> Spotlight supports both REXEC and SSH connections to Oracle servers, but raises an error when you try to open <b>simultaneous</b> REXEC and SSH connections to the same Oracle server.</p>	
Home Page / Drilldowns	<p><b>Changing column order may disable sub-pages in SQL Analyze Trace drilldown page:</b> Changing the order in which columns are displayed in the <b>Trace File Details</b> grid of the <b>Trace Files</b> page may disable the <i>Summary</i>, <i>SQL Statements</i>, and <i>SQL Statement Details</i> tabs, limiting your access to the other pages within <b>SQL Analyze Trace</b>. To counter this problem, right-click the Trace File Details grid and choose <b>Restore Default Settings</b> from the shortcut menu.</p>	
	<p>The Spotlight on Oracle Data Guard Standby icon is disabled for a connection to an instance that is part of an Oracle RAC cluster. This is by design. The metrics would not be accurate if the primary connection was not Oracle RAC. If the primary connection was to an Oracle database then the metrics would not be for the whole cluster.</p>	
	<p><b>Negative value for Shared Pool Used component:</b> The Shared Pool Used component on the Spotlight on Oracle home page may display a negative value when Oracle is first started or when the shared pool is flushed out. This occurs when the value for "shared pool free memory" in <b>v\$\$sgastat</b> is larger than the original shared pool size (Oracle bug 3288917).</p>	
	<p><b>Inaccurate value for Total RAM after network timeout error:</b> After a network timeout error, Spotlight may display an inaccurate value for the <b>Total RAM</b> metric on the Spotlight on Oracle RAC home page. When this occurs, Spotlight's calculation of Total RAM has omitted data from one or more nodes in the cluster.</p>	
	<p><b>Operating system Drilldown: (OS) statistics not reported by Spotlight on Oracle:</b> Differences between versions of operating systems mean that Spotlight is unable to collect all OS statistics in all environments. The following list shows statistics in the Operating System drilldown pages that are not reported by Spotlight on Oracle for each operating system.</p>	
	<ul style="list-style-type: none"> <li>• <b>Microsoft Windows: "Waiting" graph within CPU Utilization chart is always zero.</b> The "Waiting" graph in the CPU Utilization chart of the Operating System drilldown is included specifically to collect the relevant data from Unix systems. Windows systems do not provide the same information, and so the value of this metric is always zero for Windows systems.</li> <li>• <b>Unix AIX: Some Disk I/O and virtual memory statistics are not reported.</b> These may include disk I/O dataflows on the home page, disk read and write statistics on the Activity Summary page of the Activity drilldown, and metrics such as <i>% User</i>, <i>% Privileged</i>, <i>Work Set (MB)</i>, <i>Page faults/s</i>, <i>Handles</i>, <i>Threads</i>, <i>Start Time</i>, and <i>% Processor</i>.</li> </ul>	

- **Unix HP-UX: Missing Total RAM value on Spotlight on Oracle RAC home page:** The value for Total RAM can be displayed only if the `cstm` utility is installed and can be run on the HP-UX server.
- **Unix HP-UX: Some Disk I/O and virtual memory statistics are not reported.** These may include disk I/O dataflows on the home page, disk read and write statistics on the Activity Summary page of the Activity drilldown, and metrics such as *% User*, *% Privileged*, *Work Set (MB)*, *Page faults/s*, *Handles*, *Threads*, *Start Time*, and *% Processor*.
- **Unix HP-UX: Abnormal CPU figures.** In some cases on HP-UX Unix, CPU user time has been diagnosed at -1% to -2%, which pushes the idle time to 101% to 102%. This appears to be a bug in the HP-UX operating system, which will result in abnormal **Processor Utilization** figures in Spotlight on Oracle.
- **Linux: SUSE Linux — virtual memory statistics.** Statistics that may not be reported include *% User*, *% Privileged*, *Work Set (MB)*, *Page faults/s*, *Handles*, *Threads*, *Start Time*, and *% Processor*.
- **Linux: Red Hat Linux — invalid network metrics reported by some versions of Red Hat Linux (2.4 kernel).** Because of a known formatting bug in the output for the Unix `netstat` command, Spotlight may report inaccurate values for metrics (Network flows and Network charts, for example) that rely on `netstat`.
- **Solaris Unix: Some virtual memory statistics are not reported.** These include *% User*, *% Privileged*, *Work Set (MB)*, *Page faults/s*, *Handles*, and *Threads*.
- **Solaris Unix: No data for Paging and Scan Rates in Solaris 9 systems.** When Spotlight returns no data in the Paging and Scan Rates chart of the **OS Performance** page in the **Operating System** drilldown for a Solaris 9 system, you should apply the patch 116543-01 to that system.

**Installing and configuring DTrace scripts (Solaris 10 and later):** DTrace, a dynamic analysis tool for Sun operating systems, was first introduced in Solaris version 10. You can enable and use Spotlight's **DTrace drilldown** to capture details about the interaction between Oracle and Solaris that would otherwise be unavailable.

Before doing this, you must configure the Solaris server under investigation. To do so:

1. Locate the **SoO\_DTrace\_scripts.tar** archive package in the **Plugins\SoO** sub-folder of the Spotlight installation folder.
2. Unpack the contents of the archive to a directory on the server. Ensure that the unpacked files have **execute** permission.
3. In the **.profile** of the account that will be used to run O/S commands from Spotlight, define a `QUEST_SOO_HOME` variable that points to that directory on the server. (In previous Spotlight versions, the variable was `QUEST_HOME`.)



Feature	Known Issue	Defect ID
	<p>4. Provide that user with DTrace authority by adding the following line to <b>/etc/user_attr</b>:</p> <pre>&lt;&lt;username&gt;&gt;:::defaultpriv=basic,dtrace_proc,dtrace_kernel</pre> <p>For more information, see the <a href="#">DTrace User Guide</a>.</p>	
Predictive Diagnostics	<p><b>Predictive Diagnostics is disabled for Read Only connections.</b> Read Only databases cannot run (Predictive Diagnostics) jobs therefore no data will be gathered.</p>	ST11604
Oracle configuration	<p><b>OCI error displayed when the Oracle client setting is changed in a connection profile:</b> In some circumstances, changing the Oracle client setting within a profile can cause problems with loading the correct OCI.DLL. To resolve this issue, set the Oracle client global option to the desired client.</p> <p><b>Restarting Spotlight to change selected Oracle Home:</b> Normally, you can change the Oracle Home setting for Spotlight on Oracle whenever the selected home is NOT being used for an active Spotlight connection.</p> <p>In certain circumstances, however, disconnecting from a database causes the termination of one or more executing queries. When this happens, you can select a new Oracle Home in a connection profile (or in the Spotlight on Oracle Options window) ONLY AFTER Spotlight itself has been restarted.</p> <p><b>Unable to create or open a Spotlight connection because of missing PATH entry for Oracle client:</b></p> <ul style="list-style-type: none"> <li>You cannot create a Spotlight on Oracle connection via a specified Oracle client if that client's <b>home directory</b> is not in the Windows PATH environment variable.</li> <li>Spotlight may not connect successfully to an Oracle database if the home directory for the specified Oracle client has been removed from the PATH variable (as can happen, for example, when the PATH entry has been removed by the Oracle Universal Installer).</li> </ul> <p><b>Error when connecting to Oracle 10g database on LDAP server:</b> Spotlight may encounter access violation errors when attempting to connect to an Oracle 10g database on an LDAP 9.2.0.1 server via an Oracle 11g client. To resolve this problem, we recommend using an Oracle 10g client to connect to the 10g database.</p> <p><b>Oracle error ORA-1031 when connecting to an Oracle database:</b> To resolve the error ORA-1031: insufficient privileges in table Parameter when you try to connect to an Oracle database, add the following entry into the SQLNET.ORA file on the Spotlight client machine:</p> <pre>SQLNET.AUTHENTICATION_SERVICES= (NONE)</pre> <p><b>Note:</b> This error is seen most often for the Parameter table, but can also occur for others.</p> <p><b>Read access required to analyze Oracle trace files:</b> Before you can use Spotlight's SQL Analyze Trace facility to analyze trace files from a target Oracle database, the Spotlight OS User must have read access to the directory on the server specified by the Oracle parameter <b>UserDumpDest</b>.</p>	

Feature	Known Issue	Defect ID
	<p><b>Open_cursors parameter:</b> The <b>open_cursors</b> parameter for the database instance needs to be greater than <b>70</b> to allow Spotlight to diagnose the database instance correctly.</p>	
	<p><b>Oracle error ORA-12154 when connecting to Predictive Diagnostics with Oracle Names Server:</b> The known Oracle bug <b>#2048583</b> may cause an ORA-12154 error to be raised when you navigate to the <b>Predictive Diagnostics</b> drilldown, preventing the display of the drilldown. A possible workaround is to upgrade your Oracle client.</p>	
Oracle archiving	<p><b>Close and re-open Spotlight connections to detect new archive destinations:</b> When you add a new archive destination to a monitored Oracle database, it may not be detected by Spotlight. Disconnect from the database and then reconnect to view the details of the new archive destination.</p>	
	<p><b>Unreliable historical data for archive destinations:</b> When viewed in History mode, the Spotlight connection may on occasion display incorrect data for archive log destinations.</p>	
	<p><b>Information shown for a single node only in Alert Log and Archive Log diagnostics:</b> In a clustered environment where the <b>global_names</b> parameter is set to TRUE, alert log and archive log diagnostics within Spotlight on Oracle RAC will display data for one node only. To work around this, add the entry</p> <pre>alter session set global_names=FALSE</pre> <p>to the SPOTLIGHT.ORA file in the <b>Plug-ins\SoO</b> sub-folder of the Spotlight installation folder. This will change the <b>global_names</b> parameter for the relevant Spotlight session.</p>	
	<p><b>Limited support for Archive Destinations on mapped network drives (Windows):</b> Spotlight does not as yet calculate or display <b>Time to Failure</b> estimates for Oracle RAC systems on Windows platforms whose archive destinations are not local drives.</p>	
Oracle 12c	<p>In an Oracle 12c Data Guard environment, in some circumstances the <b>Transport Process Running alarm</b> fails to fire when log shipping is stopped.</p> <p>Spotlight on Oracle expects the Oracle process to stop when log shipping is stopped, but in some circumstances the Oracle process continues to run (idle).</p>	SoO-1759
	<p>Plugged database sessions sometimes don't show in the <b>Top sessions</b> drilldown.</p> <p>To fix the issue, run <b>alter system flush shared_pool</b></p>	SoO-1374
	<p>When the Spotlight connection is to the container database, the <b>Container</b> drop down menu may not populate with all the plugged in databases. This applies to the <b>Activity   Summary</b> and <b>Pluggable Databases   Resource Usage</b> drilldowns.</p> <p>To fix the issue, run <b>alter system flush shared_pool</b></p> <p>On Oracle RAC, run <b>alter system flush shared_pool</b> on every node of the RAC.</p>	SoO 1426
	<p>When the Spotlight connection is to the container database:</p>	SoO-1376

Feature	Known Issue	Defect ID
	<ul style="list-style-type: none"> <li>There may be <b>No Data</b> displayed on the <b>IO Throughput Requests</b> and <b>IO Latency</b> charts in the <b>Activity   Summary</b> drilldown when the selected <b>Container</b> is the plugged in database.</li> </ul> <p>When the Spotlight connection is to the plugged in database:</p> <ul style="list-style-type: none"> <li>There will be <b>No Data</b> displayed in the <b>I/O   Tablespace</b> and <b>I/O   Datafiles</b> drilldowns, and the <b>I/O   Summary</b> drilldown when <b>File Type</b> is selected.</li> <li>There will be <b>No Data</b> displayed on the <b>IO Throughput Requests</b> and <b>IO Latency</b> charts in the <b>Activity   Summary</b> drilldown.</li> </ul> <p>The problem is v\$iostat_file is empty on the pluggable database.</p>	SoO-1417
	<p>When the Spotlight connection is to the container database:</p> <ul style="list-style-type: none"> <li>There may be negative values displayed in the <b>Activity   Summary</b> drilldown when the selected <b>Container</b> is the plugged in database.</li> <li>There may be negative values displayed in the <b>Pluggable Databases</b> drilldown.</li> <li>There may be a delay in populating the <b>Container</b> drop down menu with all the plugged in databases on the <b>Activity   Summary</b> drilldown.</li> </ul> <p>When the Spotlight connection is to the plugged in database:</p> <ul style="list-style-type: none"> <li>There may be negative/incorrect (self-correcting spiked) values displayed throughout the product including the <b>Activity   Summary</b> drilldown, the <b>SQL &amp; Application Workload   Parse Activity</b> drilldown, <b>Parse Ratios</b> and <b>Parse Wait Times</b> charts, and the <b>SQL &amp; Application Workload   Sort Activity   IO Wait Times</b> chart.</li> </ul> <p>The problem is with Oracle counters not always incrementing correctly for plugged in databases.</p>	SoO-1377 SoO-1410
Oracle Exadata	<p>After heavy use of the <b>cellcli</b> utility, CPU utilization on the cell host may hit 100% and stay there. The runaway processes appear to be java and cellsvr. To fix, identify the cell host on the <b>Exadata   Cell Balance</b> drilldown then enter the following Unix command on the appropriate cell host:</p> <pre>cellcli -e "alter cell restart services MS"</pre>	
	<p><b>Windows Firewall has blocked some features of this program:</b> You may see this Windows Security Alert while Spotlight is running.</p> <ul style="list-style-type: none"> <li>Program Name (Spotlight Console) - This may occur while monitoring Oracle Exadata. Exadata Storage Cells are generally only accessible to Spotlight via SSH port forwarding. If requested, allow Spotlight to communicate over the Network via SSH Port Forwarding.</li> </ul>	PT32653067
Oracle 11g	<p><b>Spotlight support for Oracle 10g or 11g Instant Client:</b> Spotlight on Oracle supports the use of the <b>Oracle 10g</b> or <b>Oracle 11g</b> Instant Client when it is the default Oracle client, but the Oracle Instant Client may not be available in the list of Oracle clients shown in the Spotlight <b>connection profile</b> or in the <b>Oracle home</b> item in the Spotlight on Oracle Options window.</p>	

Feature	Known Issue	Defect ID
	<b>Bad data in Latch Misses chart:</b> The Latch Misses chart in the Activity Latches drilldown can show bad data for Oracle 11gR2 under category "Other". This is due to intermittent bad data being returned from Oracle for latch "JS slv state obj latch". Bug 9534870 has been raised with Oracle. Using the Filter button to remove the "Other" category from the chart is a possible workaround for this issue.	
Oracle 10g	<b>Asynchronous I/O failure in Oracle 10g (Release 2) on Linux:</b> In some Linux implementations, Oracle 10G (Release 2) is not able to report I/O activity or events to the operating system while using asynchronous I/O. This problem can cause database writer contention in Oracle and cause Spotlight to raise database writer alarms. To correct the problem, you need to stop the database and relink the base Oracle binary with the option <b>async_on</b> . <i>[For more information, see Document 365416.1 on the Oracle Metalink Web site (<a href="https://metalink.oracle.com/">https://metalink.oracle.com/</a>).]</i>	
	<b>Oracle 10g bug may affect display of SGA data:</b> A bug introduced in Oracle 10g may result in several Spotlight components – in particular, the <b>SGA Current Size</b> component on the home page, and various components on the <b>SGA Utilization</b> page of the <b>Configuration &amp; Memory</b> drilldown – to display the message " <b>Unknown – Oracle Bug</b> ". The bug responsible for causing this error has been fixed in Oracle release 10.2.0.3.	

## Known Issues - Spotlight Diagnostic Server, Spotlight Mobile and Spotlight Cloud

Feature	Known Issue	Defect ID
Spotlight Cloud user token	Spotlight does not allow for multiple Windows users (on the same computer) to enable <b>Spotlight for Mobile devices and web based analytics</b> independently. Only the last Windows user's Spotlight Cloud user token is remembered.	SoO-1520
Installation and Startup	To install the Spotlight Diagnostic Server on a computer other than the Spotlight Client the remote computer must enable the "Remote Registry" service. The remote computer is the computer remote from the Spotlight Client.  Note: By default the Remote Registry service is disabled on Windows 8.	SoO-1810
	If Spotlight on Oracle 10.3 is installed side by side with Spotlight on Oracle 10.2 or 10.1 then the Spotlight Client does not auto detect a pre existing Spotlight Diagnostic Server.  Workaround: On the Spotlight on Oracle, View   Options   Configure Diagnostic Server page: 1) Enter the host of the Spotlight Diagnostic Server, 2) Spotlight detects that an upgrade is available. Click Upgrade/Install to upgrade the Spotlight Diagnostic Server.  Alternative Workaround: On the Spotlight on Oracle, View   Options   Configure Diagnostic Server page: Reinstall the Spotlight Diagnostic Server.	SOO-2166
Spotlight Mobile	When two Diagnostic Servers use the same User Token then the Heat Map will flip back and forth between the two at various intervals.	

Feature	Known Issue	Defect ID
Monitoring Connections	<p>For connections through the Spotlight Diagnostic Server (Spotlight Cloud and Spotlight Mobile)</p> <ul style="list-style-type: none"> <li>• Oracle RAC connections to an Oracle 12c pluggable database are not supported.</li> <li>• The CPU Usage alarm on an Oracle RAC connection sometimes does not show on the Heatmap.</li> </ul>	DS-312 SoO-1894
Uninstall	<p>For Windows 8.x there may be issues using the Spotlight Client to uninstall the Spotlight Diagnostic Server.</p> <p>Workaround: For Windows 8.x use Windows Control Panel   Programs and Features. Uninstall "Spotlight Diagnostic Server for Oracle".</p>	SOO-1805

## Known Issues - Monitoring MySQL Databases

Feature	Known Issue	Defect ID
Connections	Connections to MySQL databases do not support the use of SSH public and private keys.	
Activity drilldown	<b>No data shown in Mutex page for MySQL versions 5.0.33 to 5.1.1:</b> Because the data returned by the <b>Show mutex status</b> command depends on the compile options selected for the MySQL server, this version of Spotlight on MySQL does not display mutex information for MySQL versions 5.0.33 to 5.1.1.	
Linux	<p><b>'iostat' required for full functionality on Linux systems:</b> In UNIX-based systems, Spotlight on MySQL requires access to the <b>iostat</b> program in order to display its full functionality; it will display an error if <b>iostat</b> is not available.</p> <p>A number of Linux distributions do NOT install <b>iostat</b> by default. If you encounter an "iostat command not found" error while diagnosing a MySQL database, you can either:</p> <ul style="list-style-type: none"> <li>• Click <b>Ignore</b>, in which case the error message will not appear, and <b>I/O by Disk statistics</b> will NOT be shown in the <b>OS Performance page</b> of the <b>OS Details</b> drilldown.</li> <li>• Install the <b>iostat</b> command. On Red Hat Linux this command is included in the <b>sysstat</b> package.</li> </ul>	
Spotlight home page	<b>Tablespace storage data not available without O/S user permissions to view InnoDB files:</b> Without the O/S permission to view InnoDB files, the Tablespace components in the Storage panel of the Spotlight on MySQL home page display the value <b>N/A</b> .	

# Known Issues - Monitoring Unix Operating Systems

Feature	Known Issue	Defect ID
Connections	<p><b>REXEC and SSH protocols and Unix commands:</b> Spotlight uses the <b>REXEC</b> or <b>SSH</b> protocols to submit various Unix commands (for example, netstat, vmstat, iostat, sar) to observe system activity. These commands must be accessible to an REXEC or SSH session for Spotlight to be able to observe Unix activity. If these commands are not located in the search path for REXEC or SSH sessions, Spotlight displays an error.</p> <hr/> <p><b>'iostat' command may not be installed.</b></p> <p>Spotlight on Unix works with full functionality only when the <b>iostat</b> command is installed on the server under diagnosis. This may NOT be true for all Unix systems. If <b>iostat</b> is NOT installed, Spotlight may display an error message such as <b>'iostat: command not found'</b>. If you encounter this error, you can:</p> <p>Install the <b>iostat</b> command on the server. (On Red Hat Linux, this command is included in the <b>sysstat</b> package.)</p> <hr/> <p><b>Logging on as "root".</b></p> <p>When connecting to a Unix OS, you need to do so from a logon other than "root". Remote login as "root" has been disallowed for security reasons.</p> <hr/> <p><b>Public-key cryptography available for SSH2 connections only:</b></p> <p>Spotlight can now use public-key cryptography (via DSA or RSA) to communicate securely with Unix systems, but this functionality is made available only under the SSH2 protocol.</p> <hr/> <p><b>Password authentication for SSH connections that do NOT use public-key cryptography.</b></p> <p>To allow Spotlight to make SSH connections to any Unix or Linux hosts that permit SSH connections, you may need to alter the <b>PasswordAuthentication</b> configuration item in the <b>sshd_config</b> file. Set the value of <b>PasswordAuthentication</b> to <b>yes</b>.</p> <hr/> <p><b>Password Authentication when using SSH to connect to Linux servers:</b> To allow Spotlight to make SSH connections to Linux machines via username/password authentication, you may need to set the value of the <b>PasswordAuthentication</b> configuration item in <b>/etc/ssh/sshd_config</b> to <b>yes</b>.</p>	
AIX Limitations	<p>Specific implementations of AIX may limit Spotlight's ability to collect data. These include:</p> <ul style="list-style-type: none"><li>• The <b>Procs Swapped</b> button in the Memory panel on the home page is not supported.</li><li>• The <b>Physical Memory</b> metric in the Process Details sub-page of the Processes and Services drilldown is not supported.</li></ul>	

Feature	Known Issue	Defect ID
	<ul style="list-style-type: none"> <li>• <b>I/O data unavailable before AIX 5.3.</b> For versions before AIX 5.3, disk I/O flows on the home page are disabled, as are disk read and disk write charts in drilldown pages.</li> </ul>	
HP-UX Limitations	<p>Specific implementations of HP-UX may limit Spotlight's ability to collect data. These include:</p> <ul style="list-style-type: none"> <li>• <b>Missing Physical RAM and Virtual Memory values on Spotlight home page:</b> Values for Physical RAM and Virtual Memory can be displayed only if the <code>cstm</code> utility is installed and can be run on the HP-UX server.</li> <li>• <b>Free RAM values may be incorrect.</b> Spotlight uses the "free" column in <code>vmstat(1)</code> to show the amount of free RAM. This is not strictly correct for HP-UX servers, but it is the only figure available that is in any way useful.</li> <li>• <b>I/O data unavailable.</b> Disk I/O flows on the home page are disabled, as are disk read and disk write charts in drilldown pages.</li> <li>• The <b>Physical Memory</b> metric in the Process Details sub-page of the Processes and Services drilldown is not supported.</li> </ul>	
Linux Limitations	<p>Specific implementations of Linux may limit Spotlight's ability to collect data. These include:</p> <ul style="list-style-type: none"> <li>• The <b>Procs Swapped</b> button in the Memory panel on the home page is not supported.</li> <li>• For versions of Linux based on the 2.4 kernel, Spotlight provides no information in the <b>Waiting</b> data series of the <b>CPU Utilization</b> chart on the Activity page of the Activity Summary drilldown.</li> <li>• When running with the latest version of the Linux 2.4 kernel, <b>Disk Activity</b> metrics on the home page return invalid results due to erroneous statistics being returned from <code>iostat</code> in the <code>sysstat</code> package. To overcome this problem, the OS should be updated to a 2.6 kernel.</li> <li>• In some Linux versions, Spotlight reports the virtual memory value of multi-threaded processes incorrectly. Each thread is reported as a separate process in the Processes drilldown, and the <b>Virt Mem (MB)</b> column is reported as the sum of the virtual memory values for all threads in the process.</li> <li>• With some older versions of Linux based on the 2.4 kernel, the <b>Disk Reads</b> and <b>Disk Writes</b> charts may include negative values. These charts are based on output from <code>iostat</code>, some versions of which do not return the data required by Spotlight. To resolve this issue, upgrade to a more recent version of Linux.</li> <li>• The <b>Cache</b> chart in the Memory page of the Activity Summary drilldown is not supported.</li> </ul>	
Solaris Limitations	<p><b>Unix OS commands.</b> Unix OS commands need version 5.6 of perl or later. If this is not available you should revert to using a shell script to obtain operating system data for this server. To do this, edit the file <code>ScriptConfig.ini</code> (in the <code>..\Plug-ins\DatasourceUNIX</code> sub-folder of the Spotlight installation folder) according to the</p>	

Feature	Known Issue	Defect ID
	instructions supplied in the file.	
	<p><b>Problems with diagnosing Solaris 9 machines.</b></p> <p>A number of Spotlight home page components will not be populated when Spotlight diagnoses lightly-loaded Solaris 9 machines. This is caused by the output from the <b>vmstat</b> command regularly recording a "State Change" event, which in turn resets values for the <b>vmstat</b> command. In this case, the <b>CPU</b> spinner, <b>User %</b> gauge, <b>System %</b> gauge, <b>Queue Length</b> gauge, <b>Free RAM</b> label, <b>Blocked Processes</b> button, <b>Swapped Processes</b> button, <b>Paging In</b> and <b>Paging Out</b> flows, and <b>Swapping In</b> and <b>Swapping Out</b> flows will appear grayed out.</p> <p><b>Other Solaris Limitations:</b></p> <ul style="list-style-type: none"> <li>The <b>Collisions by Network Card</b> chart in the Network page of the Activity Summary drilldown is not supported.</li> </ul>	

## Known Issues - Monitoring Windows Operating Systems

Feature	Known Issue	Defect ID
Drilldowns	<p>Error <b>Access denied</b> on the Spotlight on Windows Home Page <b>Open Sessions</b> panel and the current user is in the Administrators group on both the local and the remote machine.</p> <p>To fix this issue: Enable the AllowRemoteRPC property in the registry of the monitored system.</p> <p>[HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Control\Terminal Server]"</p> <p>AllowRemoteRPC"=dword:00000001</p> <p>or import the registry file <a href="#">AllowRemoteRPC.reg</a></p> <p><b>Processes drilldown.</b> For some versions of Microsoft Windows, the Peak Mem Usage (MB) column in the Processes grid displays bytes or kilobytes rather than megabytes.</p> <p><b>Windows 7 error.</b> When diagnosing a Windows 7 machine, the Network / TCP/IP drilldown can show errors with the text "Error 80041010: Invalid class". This is due to problems within WMI (Windows Management Interface).</p> <p><b>Windows 7 hidden partition.</b> Windows 7 is typically installed with a 200 MB hidden partition which contains the Windows Recovery Environment (WinRE). This partition is not shown on the Spotlight on Windows home page, but data for it will be displayed on the Logical Disk Activity drilldown.</p> <p><b>Missing event log message text.</b> Redesigned resource information structures within Windows may prevent Spotlight from reading the content of event log messages on Windows Server 2008 systems.</p> <p><b>Missing Open Ports page.</b> Spotlight cannot currently display the <b>Open Ports</b> page in the <b>Network</b> drilldown for Windows Server 2008 systems.</p>	PT43095851



Feature	Known Issue	Defect ID
	<p><b>Excessive event log activity.</b> If you are connecting to a machine that has an event log that is being updated excessively (more than two items being logged per minute), it is recommended that you turn off the event log feature for that system. This is because Spotlight on Windows maintains details of all event log items, which may cause the program to use an excessive level of memory.</p>	
	<p><b>Incorrect or missing NBT information.</b> When connecting to a local machine, sometimes Windows will not return the correct NBT information. This may cause the NBT flows on the main window to be dimmed. It may also cause the information in the NBT drilldown to be blank.</p>	
	<p><b>Errors in performance counters and WMI:</b> Spotlight on Oracle now reports fewer performance counter and WMI errors of the type "<b>Error 80041010: Unknown IwbemLocator.ConnectServer error</b>". It is impossible to eliminate these errors entirely if they are generated by the Windows server under diagnosis.</p>	
	<p><b>Event log size.</b> There is a 64 KB limitation to the size of event log records.</p>	
Connections	<p><b>Service Manager is not accessible</b> error on connecting to a Windows 8 or Windows 2008 server image.</p> <p>Resolution: Ensure the user on the Spotlight Client has administrator privileges on the windows server you want to monitor.</p>	SOO-34 ST14620
	<p><b>Limit to simultaneous connections.</b> It is recommended that no more than 10 simultaneous connections be executed from the same instance of Spotlight on Windows. Depending on the available system resources, the level of response will deteriorate if this number is exceeded. The number of connections possible may also be affected by option settings; for example, setting event log options to access thousands of event log items will degrade Spotlight performance and consume more memory.</p>	
	<p><b>Remote Registry service.</b> The Spotlight machine and the machine being diagnosed must have the Remote Registry service running. If you attempt to connect to a machine that has the Remote Registry service stopped, Spotlight will return the following error message:</p> <p>No Windows server called &lt;machine name&gt; could be found on the network. If the address is valid then the Remote Registry service may not be running on the remote server.</p> <p>Make sure the Remote Registry service is running on the Spotlight machine and the machine you are connecting to.</p>	
	<p><b>Connecting to a machine running PC Anywhere.</b> If a machine has PC Anywhere loaded and is using the PC Anywhere Performance Monitor extensions (from pcaperfctr.dll), Spotlight may show "query failed" messages on that connection.</p> <p>To work around this issue, unload the PC Anywhere Performance Monitor extensions from the machine..</p>	

# System Requirements

Before installing Spotlight, ensure your system meets the following minimum hardware and software requirements:

## Client Requirements

Requirement	Description
Platform	A Pentium-based or equivalent PC with: <ul style="list-style-type: none"><li>• A 1.2 GHz Processor (recommended minimum). The required processing power will increase when Spotlight diagnoses Oracle RAC clusters with many instances.</li><li>• A monitor capable of supporting a resolution of 1280x1024 or larger. (You should also set the display to use the 64K color palette [65536 colors].)</li></ul>
Memory	<b>512 megabytes of RAM (minimum)</b> . 1 gigabyte recommended. Memory consumption will increase for multiple simultaneous connections and as the number of instances in an Oracle RAC cluster increases, and will also depend on the connection options chosen.
Hard Disk Space	<b>1 gigabyte of free disk space</b> . This should exist on a local disk drive rather than a network drive. Extra disk space will be required if you choose to log historical snapshots from within Spotlight.
Operating System	Microsoft Windows Server 2012 64-bit Microsoft Windows Server 2008 64-bit R2 and above Microsoft Windows 10 32-bit and 64-bit Microsoft Windows 8 32-bit and 64-bit Microsoft Windows 7 32-bit and 64-bit
Additional Software (Monitor Oracle Database Servers)	<ul style="list-style-type: none"><li>• <b>.NET 4.0 or above</b></li><li>• <b>SQL*Net 2.3.4 or later</b>. SQL*Net enables a connection to be established to a database. The database may be local or remote. Before you start Spotlight you must have the SQL*Net connection string for the database.</li><li>• <b>Oracle Client:</b><ul style="list-style-type: none"><li>• <b>Oracle 10g [full client or instant client]</b></li><li>• <b>Oracle 11g [full client or instant client]</b></li><li>• <b>Oracle 12c [full client or instant client]</b></li></ul></li></ul> <p>Spotlight also requires that the version of the Oracle client be the same or later than the version of any Oracle database being diagnosed. For example, to connect to an Oracle 10g cluster, you must use an Oracle 10g client or later.</p>
Additional Software (Monitor MySQL Database Servers)	<b>MySQL</b> . Spotlight on MySQL supports MySQL versions 5.0.3 or later that employ the <b>InnoDB</b> storage engine. <b>With reduced functionality</b> , it also supports versions of MySQL that use other storage engines (such as <b>MyISAM</b> ). Spotlight on MySQL may NOT support versions of the MySQL server prior to 5.0.3.

# Spotlight Diagnostic Server Requirements

Requirement	Description
Platform	2 GHz Pentium Dual Core
Memory	2 GB RAM
Hard Disk Space	300 MB
Operating System	Microsoft Windows 7 (32-bit and 64-bit) Microsoft Windows 8 (32-bit and 64-bit) Microsoft Windows 10 (32-bit and 64-bit) Microsoft Windows Server 2008 (64-bit) R2 and above Microsoft Windows Server 2012 (64-bit)
Additional	.NET 4.0 or above must be installed on the Diagnostic Server.  Internet Access  A network connection between the Diagnostic Server and Spotlight on Oracle client is required during installation of the Diagnostic Server and intermittently for connection updates.  Preferably the Diagnostic Server should be installed on a Physical Machine however it can be installed on a Virtual Machine if required.  Connections to a database using an LDAP server are not supported through the Spotlight Diagnostic Server.

## Monitored Database Servers - Requirements

Requirement	Description
Oracle	<p>The following Oracle database servers are supported for database queries. (<i>You must have the Database Administrator [DBA] user ID and password for the database you want to diagnose.</i>)</p> <ul style="list-style-type: none"><li>• Oracle 10g ( Release 2)</li><li>• Oracle 11g (Release 1 or Release 2)</li><li>• Oracle 12c</li></ul> <p><b>Notes:</b></p> <ul style="list-style-type: none"><li>• When monitoring Oracle 11g Release 2 and above, to use the Spotlight User Wizard to install objects in your schema you require DBA privileges. To use the Spotlight User Wizard to setup another user to use this connection you require SYSDBA privileges.</li></ul>

Requirement	Description
	<ul style="list-style-type: none"> <li>When monitoring Oracle 11g Release 1 (and earlier) the Spotlight User Wizard installs several read-only views into the <b>SYS schema</b> of the target database when you use the wizard to create or modify a Spotlight user. Because of this, the DBA account that you use within the Spotlight User Wizard should have <b>SYSDBA privileges</b>. If the account does not have these privileges, you will be asked to provide a valid SYS account and password.</li> </ul>
Oracle RAC	Spotlight supports up to 16 instances in a cluster, with a theoretical limit of 36 instances.
Oracle Exadata Storage Servers (Cells)	<p>Spotlight monitors Exadata Storage Server (Cells) hosted on the following Operating System: Linux Kernel V2.6.</p> <p>Ensure CellCLI is in the PATH of the Operating System account on the Exadata Storage Server (Cell) hosts. This is required for Spotlight to collect performance information.</p>
Cloud Database Services	<p>Oracle Database as a Service.</p> <p>Oracle databases running on Amazon EC2.</p>
MySQL	<p>The following MySQL database servers are supported for database queries. (<i>You must have the Database Administrator [DBA] user ID and password for the database you want to diagnose.</i>)</p> <ul style="list-style-type: none"> <li>Version 5.0.3 and later.</li> </ul>

## Monitored Operating Systems (UNIX) - Requirements

Requirement	Description
Unix Servers	<p><b>Unix servers and versions.</b> Spotlight supports the following server operating systems for O/S Server queries:</p> <ul style="list-style-type: none"> <li>Oracle Solaris 9, 10, 11</li> <li>HP-UX 11i, 11i v2, 11i v3</li> <li>IBM AIX 5.2, 5.3, 6.1, 7.1</li> <li>Red Hat operating system based on Linux 2.4, 2.6 and 3.10 kernels</li> <li>SUSE operating system based on Linux 2.4, 2.6 and 3.0 kernels</li> <li>Oracle Enterprise Linux (OEL) based on Linux 2.4, 2.6 and 3.8 kernels</li> </ul>
Unix Server Software	<p><b>Unix programs.</b> The following Unix programs must be accessible to the user logged on to the Unix machine.</p> <ul style="list-style-type: none"> <li>Perl 5.x</li> <li>awk</li> <li>cat</li> <li>date</li> </ul>

Requirement	Description
	<ul style="list-style-type: none"> <li>• df</li> <li>• grep</li> <li>• ifconfig</li> <li>• iostat (not HP-UX)</li> <li>• netstat</li> <li>• ps</li> <li>• sar</li> <li>• sed</li> <li>• tr</li> <li>• uname</li> <li>• uptime</li> <li>• vmstat</li> <li>• wc</li> <li>• who</li> </ul> <p><b>For HP-UX, additionally</b></p> <ul style="list-style-type: none"> <li>• bdf</li> <li>• cstm</li> <li>• getconf</li> <li>• swapinfo</li> <li>• /usr/sbin/ioscan</li> </ul> <p><b>For AIX, additionally</b></p> <ul style="list-style-type: none"> <li>• lsattr</li> <li>• lsdev</li> <li>• lspc</li> <li>• prtconf</li> </ul> <p><b>For Solaris, additionally</b></p> <ul style="list-style-type: none"> <li>• /etc/swap</li> <li>• mpstat</li> <li>• nawk</li> <li>• prtconf</li> </ul>
Unix User Permissions and Installation Settings	<ul style="list-style-type: none"> <li>• The Unix user should have no special processing on log-on. In particular there must be no input required from the user, and nor should any special login banners be displayed.</li> </ul>

Requirement	Description
	<ul style="list-style-type: none"> <li>• On AIX, the user must be a member of the "adm" group to be able to run the <b>sar</b> command.</li> <li>• On Linux, the <b>sysstat</b> package must be installed to enable the user to get detailed disk I/O information.</li> <li>• On Linux the <b>/proc</b> filesystem must be present.</li> <li>• For connection using SSH, the <b>sshd</b> daemon must be installed and running.</li> <li>• The Unix user must have read/write access to <b>/tmp</b></li> </ul>

## Monitored Operating Systems (Windows) - Requirements

Requirement	Description
Operating Systems	<p>Microsoft Windows Server 2012 64-bit</p> <p>Microsoft Windows Server 2008 64-bit R2 and above</p> <p>Microsoft Windows 10 32-bit and 64-bit</p> <p>Microsoft Windows 8 32-bit and 64-bit</p> <p>Microsoft Windows 7 32-bit and 64-bit</p>
Administrator access	<p>Ensure your login to the Windows machine has Administrator access privileges.</p> <p>To add a new connection to the Windows machine you are currently using, ensure you are logged in to the machine with Administrator access privileges. If necessary, logout and login again.</p>
Privileges	<p>Spotlight retrieves its data from Windows performance counters and the windows registry of the monitored system. An administrator login to the Windows machine has such access.</p>
Remote connectivity	<p>To add a new connection to a Windows machine other than the one you are currently using, ensure the machine is accessible to the Spotlight client. Spotlight uses NetBIOS traffic to retrieve <b>perfmon</b> and registry information, so any firewalls between the Spotlight client and the machine being monitored must allow this traffic to pass through.</p>

## Virtualization Support

Review the following information about using Spotlight in virtual environments:

Requirement	Description
Application	Spotlight has been tested on Citrix XenApp 6.5.
Desktop (VDI)	Spotlight has been tested on desktop VMware workstations.
Server	<p>Spotlight has been tested on VMware ESX server.</p> <p>Spotlight supports Oracle Virtualization (OVM). Limited testing has been</p>

Requirement	Description
	done using Oracle VM 3.0.

**Note:**Spotlight may work in virtualization environments other than the ones in which it was tested.

## Upgrade and Compatibility

From time to time, Quest Software may make upgrades and patches available on the Internet. Upgrades will be made available from <http://software.quest.com/>. Instructions for downloading and installing upgrades are provided on the web site.

### Notes:

- When upgrading to Spotlight on Oracle 10.3.2 history data will be reset. If you would like to keep history between upgrades then you can change the folder spotlight stores history to, through Spotlight Options | storage->History Location.
- VBScript is used to detect pre-existing Spotlight installations. If for security reasons your client system is unable to execute VBScript, you can provide the UPGRADE\_EXISTING\_PRODUCT=0 property during install to bypass checking for installed Spotlights. For example:

```
msiexec.exe /i Spotlight.msi UPGRADE_EXISTING_PRODUCT=0
```

[Back to Top](#)

## Product Licensing

Spotlight is supplied with a time-limited trial key so you may test the product. When the trial key expires Spotlight reverts to a preview mode, which limits access to the Spotlight home page and one connection at a time. If you select to open a drilldown in preview mode the following message is displayed:

The current license does not allow access to this functionality.

When you enter a valid license key and authorization message in the License Viewer, you are licensed to use Spotlight on Oracle.

### To activate a purchased commercial license

1. Click **Help | About Spotlight**.
2. Click **license information**.
3. Click **Change this license**.
4. Enter the **Authorization key**.

Make sure you enter the authorization key exactly. The site message is case sensitive.

The Windows user that updates the authorization key must have administrator access to the Windows registry and write access to the **ConsoleLicenses** folder in the Spotlight installation folder.

# Getting Started

## Contents of the Release Package

The **Spotlight on Oracle** release package contains the following products:

1. Spotlight on Oracle 10.6
2. Product Documentation, including:
  - Spotlight on Oracle Getting Started Guide
  - Online Help

## Installation Instructions

Refer to the *Spotlight on Oracle Getting Started Guide* for installation instructions.

**Note:** When upgrading to Spotlight on Oracle 10.3.2 history data will be reset. If you would like to keep history between upgrades then you can change the folder spotlight stores history to, through Spotlight Options | storage->History Location.

## Globalization

This section contains information about installing and operating this product in non-English configurations, such as those needed by customers outside of North America. This section does not replace the materials about supported platforms and configurations found elsewhere in the product documentation.

This release is Unicode-enabled and supports any character set. In this release, all product components should be configured to use the same or compatible character encodings and should be installed to use the same locale and regional options. This release is targeted to support operations in the following regions: North America, Western Europe and Latin America, Central and Eastern Europe, Far-East Asia, Japan.



# About us

## We are more than just a name

We are on a quest to make your information technology work harder for you. That is why we build community-driven software solutions that help you spend less time on IT administration and more time on business innovation. We help you modernize your data center, get you to the cloud quicker and provide the expertise, security and accessibility you need to grow your data-driven business. Combined with Quest's invitation to the global community to be a part of its innovation, and our firm commitment to ensuring customer satisfaction, we continue to deliver solutions that have a real impact on our customers today and leave a legacy we are proud of. We are challenging the status quo by transforming into a new software company. And as your partner, we work tirelessly to make sure your information technology is designed for you and by you. This is our mission, and we are in this together. Welcome to a new Quest. You are invited to Join the Innovation.

## Our brand, our vision. Together.

Our logo reflects our story: innovation, community and support. An important part of this story begins with the letter Q. It is a perfect circle, representing our commitment to technological precision and strength. The space in the Q itself symbolizes our need to add the missing piece — you — to the community, to the new Quest.

## Contacting Quest

For sales or other inquiries, visit [www.quest.com/company/contact-us.aspx](http://www.quest.com/company/contact-us.aspx) or call +1 949 754-8000.

## Technical support resources

Technical support is available to Quest customers with a valid maintenance contract and customers who have trial versions. You can access the Quest Support Portal at <https://support.quest.com>.

The Support Portal provides self-help tools you can use to solve problems quickly and independently, 24 hours a day, 365 days a year. The Support Portal enables you to:

- Submit and manage a Service Request
- View Knowledge Base articles
- Sign up for product notifications
- Download software and technical documentation
- View how-to-videos
- Engage in community discussions
- Chat with support engineers online
- View services to assist you with your product

## Copyright 2018 Quest Software Inc. ALL RIGHTS RESERVED.

This guide contains proprietary information protected by copyright. The software described in this guide is furnished under a software license or nondisclosure agreement. This software may be used or copied only in accordance with the terms of the applicable agreement. No part of this guide may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording for any purpose other than the purchaser's personal use without the written permission of Quest Software Inc.

The information in this document is provided in connection with Quest Software products. No license, express or implied, by estoppel or otherwise, to any intellectual property right is granted by this document or in connection with the sale of Quest Software products. EXCEPT AS SET FORTH IN THE TERMS AND CONDITIONS AS SPECIFIED IN THE LICENSE AGREEMENT FOR THIS PRODUCT, QUEST SOFTWARE ASSUMES NO LIABILITY WHATSOEVER AND DISCLAIMS ANY EXPRESS, IMPLIED OR STATUTORY WARRANTY RELATING TO ITS PRODUCTS INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT. IN NO EVENT SHALL QUEST SOFTWARE BE LIABLE FOR ANY DIRECT, INDIRECT, CONSEQUENTIAL, PUNITIVE, SPECIAL OR INCIDENTAL DAMAGES (INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS OF PROFITS, BUSINESS INTERRUPTION OR LOSS OF INFORMATION) ARISING OUT OF THE USE OR INABILITY TO USE THIS DOCUMENT, EVEN IF QUEST SOFTWARE HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. Quest Software makes no representations or warranties with respect to the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Quest Software does not make any commitment to update the information contained in this document.

If you have any questions regarding your potential use of this material, contact:

Quest Software Inc.

Attn: LEGAL Dept

4 Polaris Way

Aliso Viejo, CA 92656

Refer to our Web site ([www.quest.com](http://www.quest.com)) for regional and international office information.

### Patents

Quest Software is proud of our advanced technology. Patents and pending patents may apply to this product. For the most current information about applicable patents for this product, please visit our website at [www.quest.com/legal](http://www.quest.com/legal).

### Trademarks

Quest, Toad, Spotlight and the Quest logo are trademarks and registered trademarks of Quest Software Inc. For a complete list of Quest marks, visit [www.quest.com/legal](http://www.quest.com/legal). All other trademarks and registered trademarks are property of their respective owners.

### Legend

**WARNING:** A WARNING icon indicates a potential for property damage, personal injury, or death.

**CAUTION:** A CAUTION icon indicates potential damage to hardware or loss of data if instructions are not followed.

An information icon indicates supporting information.

Spotlight on Oracle Release Notes

Updated - April 2018

Software Version - 10.6