



One Identity Manager 8.0.4

## LDAP Connector for CA ACF2 Reference Guide

**Copyright 2019 One Identity LLC.**

**ALL RIGHTS RESERVED.**

This guide contains proprietary information protected by copyright. The software described in this guide is furnished under a software license or nondisclosure agreement. This software may be used or copied only in accordance with the terms of the applicable agreement. No part of this guide may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording for any purpose other than the purchaser's personal use without the written permission of One Identity LLC .

The information in this document is provided in connection with One Identity products. No license, express or implied, by estoppel or otherwise, to any intellectual property right is granted by this document or in connection with the sale of One Identity LLC products. EXCEPT AS SET FORTH IN THE TERMS AND CONDITIONS AS SPECIFIED IN THE LICENSE AGREEMENT FOR THIS PRODUCT, ONE IDENTITY ASSUMES NO LIABILITY WHATSOEVER AND DISCLAIMS ANY EXPRESS, IMPLIED OR STATUTORY WARRANTY RELATING TO ITS PRODUCTS INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT. IN NO EVENT SHALL ONE IDENTITY BE LIABLE FOR ANY DIRECT, INDIRECT, CONSEQUENTIAL, PUNITIVE, SPECIAL OR INCIDENTAL DAMAGES (INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS OF PROFITS, BUSINESS INTERRUPTION OR LOSS OF INFORMATION) ARISING OUT OF THE USE OR INABILITY TO USE THIS DOCUMENT, EVEN IF ONE IDENTITY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. One Identity makes no representations or warranties with respect to the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. One Identity does not make any commitment to update the information contained in this document.

If you have any questions regarding your potential use of this material, contact:

One Identity LLC.  
Attn: LEGAL Dept  
4 Polaris Way  
Aliso Viejo, CA 92656

Refer to our Web site (<http://www.OneIdentity.com>) for regional and international office information.




**Patents**

One Identity is proud of our advanced technology. Patents and pending patents may apply to this product. For the most current information about applicable patents for this product, please visit our website at <http://www.OneIdentity.com/legal/patents.aspx>.

**Trademarks**

One Identity and the One Identity logo are trademarks and registered trademarks of One Identity LLC. in the U.S.A. and other countries. For a complete list of One Identity trademarks, please visit our website at [www.OneIdentity.com/legal](http://www.OneIdentity.com/legal). All other trademarks are the property of their respective owners.

**Legend**

-  **WARNING:** A WARNING icon indicates a potential for property damage, personal injury, or death.
-  **CAUTION:** A CAUTION icon indicates potential damage to hardware or loss of data if instructions are not followed.
-  **IMPORTANT, NOTE, TIP, MOBILE, or VIDEO:** An information icon indicates supporting information.

# Contents

<b>Initializing and Configuring the LDAP Connector for CA ACF2</b> .....	<b>4</b>
Pre-requisites .....	4
Platform Support .....	5
Operating Constraints .....	5
How to initialize and configure the ACF2 LDAP connector .....	5
System Variables .....	7
Domain Filter Setting .....	7
User Mapping Information .....	8
Mandatory ACF2 User Attributes .....	9
Property Mapping Rules .....	9
Object Matching Rules .....	11
Sample User Mapping .....	11
<b>Appendix: ACF2 Attributes</b> .....	<b>13</b>
<b>About us</b> .....	<b>21</b>
Contacting us .....	21
Technical support resources .....	21

# Initializing and Configuring the LDAP Connector for CA ACF2

This document describes how to initialize and configure the ACF2 LDAP connector into an existing One Identity Manager system. This enables One Identity Manager to access, read and update data stored in an ACF2 database on an IBM mainframe.

## Detailed information about this topic

- [Pre-requisites](#) on page 4
- [Platform Support](#) on page 5
- [Operating Constraints](#) on page 5
- [How to initialize and configure the ACF2 LDAP connector](#) on page 5
- [Domain Filter Setting](#) on page 7
- [System Variables](#) on page 7
- [User Mapping Information](#) on page 8
- [Appendix: ACF2 Attributes](#) on page 13

## Pre-requisites

- The IBM mainframe must have the CA LDAP Server for z/OS installed and configured. It is recommended to remove the search size limit on the CA LDAP Server. This is done by editing the configuration file `slapd.conf` on the server. Set the `sizelimit` value to "unlimited" as follows.

For versions of CA LDAP Server version 14 or earlier

```
sizelimit 0
```

For versions of CA LDAP Server version 15 or later

```
sizelimit unlimited
```

- An LDAP service account must be created on your ACF2 server which has the appropriate permissions to administer users and groups on this platform. The

account must be given sufficient privileges so that the profiles being administered fall within the "SCOPE" of the Admin user.

- 1 **NOTE:** Before attempting to connect to the CA LDAP Server with the One Identity Manager connector, it is recommended to first check that the CA LDAP server is running correctly. This can be tested with any LDAP browser for example the LDP.exe tool from Microsoft. For more information, see your LDAP browser documentation.

## Platform Support

- The ACF2 LDAP connector has been verified for synchronization against the IBM mainframe running CA ACF2 version 9.0 or later.

## Operating Constraints

- There is an eight character limit for user names on ACF2.
- There is an eight character limit for passwords on ACF2.

## How to initialize and configure the ACF2 LDAP connector

- 1 **NOTE:** The following sequence describes how you configure a synchronization project if the Synchronization Editor is in expert mode.

### ***To set up initial synchronization project for ACF2***

1. Start the Synchronization Editor and log in.
2. From the start page, select **Start a new synchronization project**.  
This starts the Synchronization Editor's project wizard.
3. Select **ACF2 LDAP Connector** on the **Choose target system** page.
4. On the **System access** page, click **Next**.
5. On the **Create system connection** page, select **Create new system connection**.
6. On the system connection wizard start page, click **Next**.

7. On the **Network** page:
  - a. In the **Server** field, enter the DNS name or IP address of your mainframe server.
  - b. In the **Port** field, enter the port number.
  - c. Click on the **Test** button to make sure the server is accessible.
  - d. The CA LDAP Server for z/OS supports LDAP v3. Enter the number 3 in the **Protocol version**.
  - e. If SSL is to be used, check the **Use SSL** box.
8. On the **Authentication** page:
  - a. Set the **Authentication method** to "Basic".
  - b. In the **Credentials** section, enter the full DN and password of the administrator account on your ACF2 system. The account DN can take the format CN=<account id> or acf2lid=<account id>.
  - c. Click **Test** to check that the credentials are valid.
9. The schema will be loaded from the ACF2 system.
10. Ignore the **Define virtual classes** page. Click **Next**.
11. On the **Search options** page:
  - a. In the **Base DN** drop-down list, select the correct base DN for your system.
  - b. Ignore **Use partitioned search**.
12. Ignore the **Modification capabilities** page. Click **Next**.
13. Ignore the **Auxiliary class assignment** page. Click **Next**.
14. On the **System attributes** page, in the **Revision properties** section, deselect the "createTimestamp" and "modifyTimestamp" entries by double clicking on them.
15. Ignore the **Select dynamic group attributes** page. Click **Next**.
16. Ignore the **Password settings** page. Click **Next**.
17. Click **Finish**.

This takes you back to the Synchronization Editor's project wizard.
18. Enter the database connection data on the **One Identity Manager connection** page.
19. This will load the ACF2 schema into your One Identity Manager. Wait for this to complete.
20. On the **Select project template** page, select **Create blank project**.
21. On the **General** page, enter a display name for your synchronization project and set a scripting language if required.
22. Click **Finish** to complete the project wizard.
23. Select **Activate project** to activate the project.

## Related Topics

- [Domain Filter Setting](#) on page 7
- [User Mapping Information](#) on page 8

# System Variables

The following system variables need to be defined for the attribute mappings. For more detailed information about variables, see the One Identity Manager Target System Synchronization Reference Guide.

**Table 1: System variables**

Name	Value
IdentDomain	The name of your ACF2 domain e.g. MAINFRAME2
UserLocation	Parent DN of your ACF2 user container, e.g. acf2ad-mingrp=lids,host=mainframe2,o=mycompany,c=com

## Related Topics

- [Domain Filter Setting](#) on page 7
- [Property Mapping Rules](#) on page 9

# Domain Filter Setting

A domain filter needs to be created to identify information that has been retrieved from the ACF2 database to keep it separate from other imported data.

1. Update the One Identity Manager schema so that all entries are included.
  - a. In the Synchronization Editor, open your ACF2 project.
  - b. Select the category **Configuration | One Identity Manager connection**.
  - c. Then in the "General" section on the right-hand side, click **Update schema**.
  - d. Click on **Yes** in the next two dialog boxes.
  - e. Click **Ok** when completed.
2. In the Manager
  - a. Select the category **LDAP | Domains**.
  - b. In the result list toolbar, click .

- c. Enter at least the following general master data on the **General** tab.

**Table 2: Domain Master Data**

Property	Description
Display name	Display name e.g. ACF2 Domain
Distinguished name	Distinguished name of the domain e.g. host=mainframe2,o=mycompany,c=com
Domain	Domain name e.g. MAINFRAME2
Structural object class	Structural object class representing the object type, enter DCOBJECT

- d. Save the changes.
3. In the Synchronization Editor, open your ACF2 project.
    - a. Select the category **Configuration | One Identity Manager connection**.
    - b. Select the **Scope view** and click **Edit scope**.
    - c. Select the object type LDAPDomain in the **Scope hierarchy** list and set the **Object filter** to: Ident\_Domain ='\$IdentDomain\$'.
    - d. Save the changes.

For more detailed information about scopes, see the One Identity Manager Target System Synchronization Reference Guide.

## Related Topics

- [System Variables](#) on page 7

# User Mapping Information

This section shows a possible mapping between a user account in ACF2 and the standard One Identity Manager database table called LDAPAccount.

- Set up a new mapping from LDAPAccount(a11) to acf21id(a11).

For more detailed information about setting up mappings, see the One Identity Manager Target System Synchronization Reference Guide.

## Detailed information about this topic

- [Mandatory ACF2 User Attributes](#) on page 9
- [Property Mapping Rules](#) on page 9



- [Object Matching Rules](#) on page 11
- [Sample User Mapping](#) on page 11

## Mandatory ACF2 User Attributes

When creating a user in the ACF2 database, the following LDAP attributes must be defined:

- objectclass
- acf2lid
- userPassword

### Related Topics

- [Property Mapping Rules](#) on page 9
- [Object Matching Rules](#) on page 11

## Property Mapping Rules

- CanonicalName ← vrtEntryCanonicalName  
vrtEntryCanonicalName is a virtual property, set to the canonical name of the object in the connector.  
Sample value:  
COM/MYCOMPANY/MAINFRAME2/LIDS/USER1234
- cn ← → acf2lid  
On the ACF2 system, acf2lid is the user ID.  
Sample value:  
USER1234
- DistinguishedName ← vrtEntryDN  
vrtEntryDN is a virtual property, set to the DN of the object in the connector. Once this mapping rule has been created, edit the mapping rule by clicking on it. Then check the box marked **Force mapping against direction of synchronization**.  
Sample value:  
acf2lid=USER1234,acf2admingrp=lids,host=mainframe2,o=mycompany,c=com
- ObjectClass ← → objectClass  
The objectClass attribute (multi-valued) on the ACF2 system. Activate the check box **Ignore case sensitivity**.  
Sample value:

ACF2LID

- StructuralObjectClass ← vrtStructuralObjectClass

vrtStructuralObjectClass on the ACF2 system defines the single object class for the object type.

Sample value:

ACF2LID

- UID\_LDPPDomain ← vrtIdentDomain

Create a fixed value property variable on the ACF2 side called vrtIdentDomain that is set to the value \$IdentDomain\$. Map this to UID\_LDPPDomain. This will cause a conflict and the Property Mapping Rule Conflict Wizard opens automatically.

### **To solve the conflict**

1. In the Property Mapping Rule Conflict Wizard, select the first option and click **OK**.
2. On the **Select an element...** page, select **Ident\_Domain** and click **OK**.
3. Confirm the security prompt with **OK**.
4. On the Edit property... page,
  - a. Deactivate **Save unresolvable keys**.
  - b. Activate **Handle failure to resolve as error**.
  - c. To close the Property Mapping Rule Conflict Wizard, click **OK**.

Sample value:

MAINFRAME2

- vrtParentDN → vrtEntryParentDN

Create a fixed value property variable on the One Identity Manager side called vrtParentDN equal to a fixed string with value \$UserLocation\$. Map this to vrtEntryParentDN on the ACF2 side.

Sample value:

acf2admingrp=lids,host=mainframe2,o=mycompany,c=com

- vrtRDN → vrtEntryRDN

Create a new variable on the One Identity Manager side of type "Format Defined Property" with name vrtRDN. Set its value to acf2lid=%CN%. Then map this to vrtEntryRDN on the ACF2 side.

Sample value:

acf2lid=USER1234

- userPassword → userPassword

Used to change a user's ACF2 password. A condition needs to be set on this rule to map the password only when there is a value to be copied.

### **To add a condition**

1. Create the mapping.
2. Edit the property mapping rule.
3. Expand the **Condition for execution** section at the bottom of the dialog.
4. Click on **Add condition** and set the following condition (a blank password is indicated by using two apostrophe characters).

```
Left.UserPassword<>' '
```


## **Related Topics**

- [Mandatory ACF2 User Attributes](#) on page 9
- [System Variables](#) on page 7
- [Object Matching Rules](#) on page 11
- [Sample User Mapping](#) on page 11

## **Object Matching Rules**

- DistinguishedName (primary rule) vrtEntryDN  
vrtEntryDN is a virtual property, set to the DN of the object in the connector. This forms a unique ID to distinguish individual user objects on the ACF2 system.

### **To convert this mapping into an object matching rule**

1. Select the property mapping rule in the rule window.
2. Click  in the rule view toolbar.  
A message appears.
3. Click **Yes** to convert the property mapping rule into an object matching rule and save a copy of the property mapping rule.

Sample value:

```
acf2lid=USER1234,acf2admingrp=lids,host=mainframe2,o=mycompany,c=com
```

## **Related Topics**

- [Mandatory ACF2 User Attributes](#) on page 9
- [Property Mapping Rules](#) on page 9
- [Sample User Mapping](#) on page 11

## **Sample User Mapping**

The following figure shows the above user mapping in operation.

### Object matching rules



Schema property in One Identity Manager	Information	Schema property in the target system
DistinguishedName	Primary rule	vrtEntryDN

### Property mapping rules



Schema property in One Identity Manager	Information	Schema property in the target system
CanonicalName	←	vrtEntryCanonicalName
cn	←	→ acf2lid
DistinguishedName	←	vrtEntryDN
ObjectClass	←	→ objectClass
StructuralObjectClass	←	vrtStructuralObjectClass
VRT_UID_LDAPDomain	←	vrtIdentDomain
UserPassword	← ?	→ userPassword
vrtParentDN		→ vrtEntryParentDN
vrtRDN		→ vrtEntryRDN

## Appendix: ACF2 Attributes

The following table lists the ACF2 attributes that are made available to One Identity Manager by the ACF2 LDAP connector.

**Table 3: List of ACF2 Attributes**

<b>Attribute Name</b>
AccessCount
AccessDate
AccessRileMustValidate
AccessShiftName
AccessSource
AccessSourceName
AccessTime
AccessZoneName
ACF2AccountPriv
ACF2AuditPriv
ACF2CICSSecurity
ACF2ConsultPriv
ACF2DynamicPrivileges
ACF2LeaderPriv
acf2lid
ACF2RefreshPriv
ACF2SecurityPriv
ActiveDate

**Attribute Name**

---

AllowJOBFROMStmntUsage

---

AuthSubmissionPgm

---

AutomaticDump

---

BatchJobAuthority

---

BulkDataTransfer

---

BypassCmdLimiting

---

BypassManVioProcessing

---

BypassMusassAccessStats

---

BypassStepMustComplete

---

BypassTapeLabelLimited

---

BypassTapeLabelProcessing

---

BypassTSOCmdList

---

CancelDate

---

CICSAccess

---

CICSControlRecSYSID

---

CICSMultipleSignons

---

CICSOpClass

---

CICSOpId

---

CICSPriority

---

CICSRsrcAccessKey

---

CICSSecKey1-3

---

CICSSecKeyLast5

---

CICSTargetUsage

---

DDBHomenode

---

DoNotStoreACF2Rules

---

EUARoutine1

---

EUARoutine2

---

EUARoutine3

---

EUARoutine4

**Attribute Name**

EUARoutine5

EUARoutine6

EUARoutine7

EUARoutine8

ExpirePassword

FullName

GeneralIDMSAccess

GeneralIMSAccess

GeneralTSOAccess

GeneralVAXAccess

GeneralVMAccess

GeneralVM-ESAAccess

GenerateDumps

GroupName

HasAccesToSystem

HomeDirectory

IdleTime

IDMSClistVersion

IDMSMusassOpts10-2

IDMSMusassStartPgm

IDMSSignonClist

InvalidPswdDate

InvalidPswdTime

KerberosCruV

KerberosVios

LastUpdatedDateTime

LDAPDirectorySync

LidExpireDate

LIDTEMP

## Attribute Name

---

LIDZMAX

---

LIDZMIN

---

LinuxName

---

LogAccessOutsideShift

---

LogActiveLibBatchAccess

---

LogActiveLibBatchAccessVios

---

LotusName

---

MaintPrivilege

---

MaxAddrSpaceSize

---

MaxCPUTime

---

MaxDataSpacePages

---

MaxDaysBetweenPswdChange

---

MonitorLogon

---

MonitorLogonSecurityAlert

---

MountDevices

---

MusassDefaultLid

---

MusassID

---

MusassInfoCall

---

MusassLid

---

MusassUpdateAuth

---

NonCancelPrivilege

---

NovellName

---

NumericUserID

---

PasswordForExtract

---

PCFControl

---

Phone

---

PrefixTSOMessages

---

PromptForMissingParms

---

PswdChgDateTime



**Attribute Name**

PswdEntrySource

PSWD-MIX

PSWD-MX8

PSWD-UPP

PswdViolations

PTICKET

ReadAccessToAll

ReceiveTSOMailMsgs

ReceiveTSOMessages

ReceiveTSONotices

RecentPswdViolations

RestrictedLogonid

RsrcRuleMustValidate

RuleKeyPrefix

ScopeList

SecurityViolations

ShellProgram

SMSDefaultValues

SpecifyTSOAcctNum

SpecifyTSOLogonSize

SpecifyTSOLogonTime

SpecifyTSOLogonUnit

SpecifyTSOMsgClass

SpecifyTSOOutputDest

SpecifyTSOPerformance

SpecifyTSOProcedure

SpecifyTSORecover

StartedTaskAccess

SubmitJobThruAPFOnly

**Attribute Name**

---

SuspendedLid

---

SynchronizedLogonNode

---

SYSPEXCL

---

TargetNodes

---

TraceAllEvents

---

TraceTSOCommands

---

TSOAccountPriv

---

TSOAccountRequired

---

TSOCommandListModule

---

TSOConsole

---

TSODefaultAccount

---

TSODefaultPerformance

---

TSODefaultProcedure

---

TSODefaultRegionSize

---

TSODefaultTime

---

TSODefaultUnit

---

TSODelChar

---

TSOFullScreenLogon

---

TSOHoldClass

---

TSOLineDelChar

---

TSOMailIndexRecordPtr

---

TSOModalMsgs

---

TSOMsgClass

---

TSOMsgPause

---

TSOOperator

---

TSOPrefix

---

TSOProcedureRequired

---

TSORecover

---

TSORegionSizeMax

**Attribute Name**

TSOSubmitAuthority

TSOSubmitClass

TSOSysoutClass

TSOSysoutDest

UnicenterTNGSync

UseProtectedPrograms

UserCancelled

UserIdentificationString

userPassword

UserWhoSetCancel

UsingLID

ValidateRestrictAccess

ValidateTSOAccount

ValidateTSOProcedure

VMAutologAll

VMAutologNoPswd

VMAutologOnly

VMBypassDialValidation

VMDefaultAccount

VMDiagnose84

VMGroupLogonId

VMIdleMinutes

VMIssueD4Diagnose

VMLastLogonId

VMNoSpoolFoundAction

VMOptionalGroupId

VMPVMAccess

VMSAFDiagnose

VMSFS

**Attribute Name**

---

VMSRFAccess

---

VMSRFAccessFromVSE

---

VMSyntaxErrorAction

---

VMTargetDiagnose

---

VMTargetDiagnoseReset

---

VMTempRuleMustExit

---

VMValidateAccounting

One Identity solutions eliminate the complexities and time-consuming processes often required to govern identities, manage privileged accounts and control access. Our solutions enhance business agility while addressing your IAM challenges with on-premises, cloud and hybrid environments.

## Contacting us

For sales or other inquiries, such as licensing, support, and renewals, visit <https://www.oneidentity.com/company/contact-us.aspx> or call +1-800-306-9329.

## Technical support resources

Technical support is available to One Identity customers with a valid maintenance contract and customers who have trial versions. You can access the Support Portal at <https://support.oneidentity.com/>.

The Support Portal provides self-help tools you can use to solve problems quickly and independently, 24 hours a day, 365 days a year. The Support Portal enables you to:

- Submit and manage a Service Request
- View Knowledge Base articles
- Sign up for product notifications
- Download software and technical documentation
- View how-to videos at [www.YouTube.com/OneIdentity](http://www.YouTube.com/OneIdentity)
- Engage in community discussions
- Chat with support engineers online
- View services to assist you with your product