



syslog-ng Store Box 6.0.2

Packaging Checklist

## Copyright 2021 One Identity LLC.

### ALL RIGHTS RESERVED.

This guide contains proprietary information protected by copyright. The software described in this guide is furnished under a software license or nondisclosure agreement. This software may be used or copied only in accordance with the terms of the applicable agreement. No part of this guide may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording for any purpose other than the purchaser's personal use without the written permission of One Identity LLC .

The information in this document is provided in connection with One Identity products. No license, express or implied, by estoppel or otherwise, to any intellectual property right is granted by this document or in connection with the sale of One Identity LLC products. EXCEPT AS SET FORTH IN THE TERMS AND CONDITIONS AS SPECIFIED IN THE LICENSE AGREEMENT FOR THIS PRODUCT, ONE IDENTITY ASSUMES NO LIABILITY WHATSOEVER AND DISCLAIMS ANY EXPRESS, IMPLIED OR STATUTORY WARRANTY RELATING TO ITS PRODUCTS INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT. IN NO EVENT SHALL ONE IDENTITY BE LIABLE FOR ANY DIRECT, INDIRECT, CONSEQUENTIAL, PUNITIVE, SPECIAL OR INCIDENTAL DAMAGES (INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS OF PROFITS, BUSINESS INTERRUPTION OR LOSS OF INFORMATION) ARISING OUT OF THE USE OR INABILITY TO USE THIS DOCUMENT, EVEN IF ONE IDENTITY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. One Identity makes no representations or warranties with respect to the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. One Identity does not make any commitment to update the information contained in this document.

If you have any questions regarding your potential use of this material, contact:

One Identity LLC.  
Attn: LEGAL Dept  
4 Polaris Way  
Aliso Viejo, CA 92656

Refer to our Web site (<http://www.OneIdentity.com>) for regional and international office information.

### Patents

One Identity is proud of our advanced technology. Patents and pending patents may apply to this product. For the most current information about applicable patents for this product, please visit our website at <http://www.OneIdentity.com/legal/patents.aspx>.

### Trademarks

One Identity and the One Identity logo are trademarks and registered trademarks of One Identity LLC. in the U.S.A. and other countries. For a complete list of One Identity trademarks, please visit our website at [www.OneIdentity.com/legal](http://www.OneIdentity.com/legal). All other trademarks are the property of their respective owners.

### Legend

 **WARNING:** A WARNING icon highlights a potential risk of bodily injury or property damage, for which industry-standard safety precautions are advised. This icon is often associated with electrical hazards related to hardware.

 **CAUTION:** A CAUTION icon indicates potential damage to hardware or loss of data if instructions are not followed.

SSB Packaging Checklist  
Updated - 11 January 2021, 09:44  
Version - 6.0.2

# Contents

<b>Package contents inventory</b> .....	<b>4</b>
<b>syslog-ng Store Box Hardware Installation Guide</b> .....	<b>5</b>
<b>Installing the SSB hardware</b> .....	<b>6</b>
<b>Hardware specifications</b> .....	<b>9</b>
<b>About us</b> .....	<b>10</b>
Contacting us .....	10
Technical support resources .....	10

# Package contents inventory

Carefully unpack all server components from the packing cartons. The following items should be packaged with the syslog-ng Store Box:

- A syslog-ng Store Box appliance, pre-installed with the latest syslog-ng Store Box firmware.
- syslog-ng Store Box accessory kit, including the following:
  - syslog-ng Store Box 6.0 Packaging Checklist (this document).
  - GPL v2.0 license.
- Rack mount hardware.
- Power cable.

The default BIOS and IPMI passwords are in the documentation.

## syslog-ng Store Box Hardware Installation Guide

This section describes how to set up the syslog-ng Store Box (SSB) hardware. Refer to the following documents for step-by-step instructions:

- *syslog-ng Store Box Appliance 3000*: see the *SC113 Chassis Series User's Manual, Chapter 6: Rack Installation*, available online at <https://www.supermicro.com/manuals/chassis/1U/SC113.pdf>.
- *syslog-ng Store Box Appliance 3500*: see the *SuperServer 1029U-T Series User's Manual, Chapter 2: Server Installation*, available online at <https://www.supermicro.com/manuals/superserver/1U/MNL-1973.pdf>.

The manuals are also available online at the [syslog-ng Store Box Documentation page](#). Note that SSB hardware is built to custom specifications: CPU, memory, network card, and storage options differ from the stock chassis. You can find the hardware specifications in [Hardware specifications](#)

- For details on how to install a single SSB unit, see [Installing the SSB hardware](#).
- For details on how to install two SSB units in high availability mode, see [Installing two SSB units in HA mode](#).

# Installing the SSB hardware

This section describes how to install a single SSB unit.

## To install a single SSB unit

1. Unpack SSB.
2. *Optional step:* Install SSB into a rack with the slide rails. Slide rails are available for all SSB appliances.
3. Connect the cables.

### a. For general networks

Connect the Ethernet cable facing your LAN to the Ethernet connector labeled as 1. This is the external interface of SSB. This interface is used for the initial configuration of SSB, and for communication between SSB and the clients. (For details on the roles of the different interfaces, see ["Network interfaces" in the Administration Guide.](#))

### For 10Gbit-only networks

Connect the cable facing your LAN to the SFP+ connector labeled as A. This is the external interface of SSB. This interface is used for the initial configuration of SSB, and for communication between SSB and the clients. (For details on the roles of the different interfaces, see ["Network interfaces" in the Administration Guide.](#))



#### NOTE:

For a list of compatible connectors, see [Linux\\* Base Driver for 10 Gigabit Intel® Ethernet Network Connection Overview](#). Note that SFP transceivers encoded for non-Intel hosts may be incompatible with the Intel 82599EB host chipset found in SSB.



#### CAUTION:

**Do not leave any unused SFP/SFP+ transceiver in the 10Gbit interface. It may cause network outage.**

- b. Connect an Ethernet cable that you can use to remotely support the SSB hardware to the IPMI interface of SSB. For details, see the following documents:

For syslog-ng Store Box Appliance 3000 and 3500, see the [IPMI User's Guide](#).



#### CAUTION:

**Connect the IPMI before plugging in the power cord. Failing to do so will result in IPMI failure.**

**⚠ CAUTION: SECURITY HAZARD!**

The IPMI interface, like all out-of-band management interfaces, has known vulnerabilities that One Identity cannot fix or have an effect on. To avoid security hazards, One Identity recommends that you only connect the IPMI interface to well-protected, separated management networks with restricted accessibility. Failing to do so may result in an unauthorized access to all data stored on the SSB appliance. Data on the appliance can be unencrypted or encrypted, and can include sensitive information, for example, passwords, decryption keys, private keys, and so on.

For more information, see [Best Practices for managing servers with IPMI features enabled in Datacenters](#).

**📘 NOTE:**

The administrator of SSB must be authorized and able to access the IPMI interface for support and troubleshooting purposes in case vendor support is needed.

The following ports are used by the IPMI interface:

- Port 623 (UDP): IPMI (cannot be changed)
  - Port 5123 (UDP): floppy (cannot be changed)
  - Port 5901 (TCP): video display (configurable)
  - Port 5900 (TCP): HID (configurable)
  - Port 5120 (TCP): CD (configurable)
  - Port 80 (TCP): HTTP (configurable)
- c. *Optional step:* Connect the Ethernet cable to be used for managing SSB after its initial configuration to the Ethernet connector labeled as 2. This is the management interface of SSB. (For details on the roles of the different interfaces, see "[Network interfaces](#)" in the [Administration Guide](#).)
- d. *Optional step:* Connect the Ethernet cable connecting SSB to another SSB node to the Ethernet connector labeled as 4. This is the high availability (HA) interface of SSB. (For details on the roles of the different interfaces, see "[Network interfaces](#)" in the [Administration Guide](#).)
4. Power on the hardware.
  5. Change the BIOS password on the syslog-ng Store Box. The default password is ADMIN or changeme, depending on your hardware.
  6. Change the IPMI password on the syslog-ng Store Box. The default password is ADMIN or changeme, depending on your hardware.

**NOTE:**

Ensure that you have the latest version of IPMI firmware installed. You can download the relevant firmware from the One Identity Knowledge Base:

- [IPMI firmware for syslog-ng Store Box Appliance 3000](#)
- [IPMI firmware for syslog-ng Store Box Appliance 3500](#)
- [IPMI firmware for syslog-ng Store Box T1](#)
- [IPMI firmware for IPMI firmware for syslog-ng Store Box T4](#)
- [IPMI firmware for IPMI firmware for syslog-ng Store Box T10](#)

To change the IPMI password, connect to the IPMI remote console.

**NOTE:**

If you encounter issues when connecting to the IPMI remote console, add the DNS name or the IP address of the IPMI interface to the exception list (whitelist) of the Java console. For details on how to do this, see the Java FAQ entry titled [How can I configure the Exception Site List?](#)

7. Following boot, SSB attempts to receive an IP address automatically via DHCP. If it fails to obtain an automatic IP address, it starts listening for HTTPS connections on the 192.168.1.1 IP address.

To configure SSB to listen for connections on a custom IP address, complete the following steps:

- a. Access SSB from the local console, and log in with username root and password default.
- b. In the Console Menu, select **Shells > Core shell**.
- c. Change the IP address of SSB:

```
ip addr add <IP-address>/24 dev eth0
```

Replace <IP-address> with an IPv4 address suitable for your environment.

- d. Set the default gateway using the following command:

```
ip route add default via <IP-of-default-gateway>
```

Replace <IP-of-default-gateway> with the IP address of the default gateway.

- e. Type exit, then select **Logout** from the Console Menu.
8. Connect to the SSB web interface from a client machine and complete the Welcome Wizard as described in ["The Welcome Wizard and the first login" in the Administration Guide](#).

**NOTE:**

The syslog-ng Store Box Administrator Guide is available on the [syslog-ng Store Box Documentation page](#).



## Hardware specifications

The syslog-ng Store Box (SSB) appliances are built on high performance, energy efficient, and reliable hardware that are easily mounted into standard rack mounts.

For detailed hardware specifications of your appliance, see ["Hardware specifications" in the Installation Guide](#).

One Identity solutions eliminate the complexities and time-consuming processes often required to govern identities, manage privileged accounts and control access. Our solutions enhance business agility while addressing your IAM challenges with on-premises, cloud and hybrid environments.

## Contacting us

For sales and other inquiries, such as licensing, support, and renewals, visit <https://www.oneidentity.com/company/contact-us.aspx>.

## Technical support resources

Technical support is available to One Identity customers with a valid maintenance contract and customers who have trial versions. You can access the Support Portal at <https://support.oneidentity.com/>.

The Support Portal provides self-help tools you can use to solve problems quickly and independently, 24 hours a day, 365 days a year. The Support Portal enables you to:

- Submit and manage a Service Request
- View Knowledge Base articles
- Sign up for product notifications
- Download software and technical documentation
- View how-to videos at [www.YouTube.com/OneIdentity](http://www.YouTube.com/OneIdentity)
- Engage in community discussions
- Chat with support engineers online
- View services to assist you with your product