



One Identity Manager

Operations Support Web Portal User Guide

Copyright 2022 One Identity LLC.

ALL RIGHTS RESERVED.

This guide contains proprietary information protected by copyright. The software described in this guide is furnished under a software license or nondisclosure agreement. This software may be used or copied only in accordance with the terms of the applicable agreement. No part of this guide may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording for any purpose other than the purchaser's personal use without the written permission of One Identity LLC .

The information in this document is provided in connection with One Identity products. No license, express or implied, by estoppel or otherwise, to any intellectual property right is granted by this document or in connection with the sale of One Identity LLC products. EXCEPT AS SET FORTH IN THE TERMS AND CONDITIONS AS SPECIFIED IN THE LICENSE AGREEMENT FOR THIS PRODUCT, ONE IDENTITY ASSUMES NO LIABILITY WHATSOEVER AND DISCLAIMS ANY EXPRESS, IMPLIED OR STATUTORY WARRANTY RELATING TO ITS PRODUCTS INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT. IN NO EVENT SHALL ONE IDENTITY BE LIABLE FOR ANY DIRECT, INDIRECT, CONSEQUENTIAL, PUNITIVE, SPECIAL OR INCIDENTAL DAMAGES (INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS OF PROFITS, BUSINESS INTERRUPTION OR LOSS OF INFORMATION) ARISING OUT OF THE USE OR INABILITY TO USE THIS DOCUMENT, EVEN IF ONE IDENTITY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. One Identity makes no representations or warranties with respect to the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. One Identity does not make any commitment to update the information contained in this document.

If you have any questions regarding your potential use of this material, contact:

One Identity LLC.
Attn: LEGAL Dept
4 Polaris Way
Aliso Viejo, CA 92656

Refer to our Web site (<http://www.OneIdentity.com>) for regional and international office information.

Patents

One Identity is proud of our advanced technology. Patents and pending patents may apply to this product. For the most current information about applicable patents for this product, please visit our website at <http://www.OneIdentity.com/legal/patents.aspx>.

Trademarks

One Identity and the One Identity logo are trademarks and registered trademarks of One Identity LLC. in the U.S.A. and other countries. For a complete list of One Identity trademarks, please visit our website at www.OneIdentity.com/legal. All other trademarks are the property of their respective owners.

Legend

 **WARNING:** A WARNING icon highlights a potential risk of bodily injury or property damage, for which industry-standard safety precautions are advised. This icon is often associated with electrical hazards related to hardware.

 **CAUTION:** A CAUTION icon indicates potential damage to hardware or loss of data if instructions are not followed.

Contents

Operations Support Web Portal	5
An overview of the functions	6
The user interface layout	7
Structure of the Operations Support Web Portal	8
Logging in and out	10
System information	11
Displaying system data	11
Searching	13
Running a search	14
Object history	15
Displaying object histories	16
Displaying Job queue and DBQueue tasks	17
Creating passcodes for identities	19
Managing passwords for identities	20
Status reports	21
Availability check	21
Check service availability	22
Manage processes	23
Process overview	23
Process details	24
Viewing processes and details	25
Failed processes	25
Displaying failed Job queue processes	25
Handling failed processes	26
Process steps	27
Viewing process steps	27
Performance	28

Viewing performance	28
Synchronization	29
The synchronization project log	30
Viewing synchronization status and log	30
Displaying a synchronization report	31
Post-processing outstanding objects	32
Displaying outstanding objects	33
Deleting outstanding objects	33
Resetting outstanding objects	34
Adding outstanding objects to the target system	34
Unresolved references	36
Displaying unresolved references	37
Database log	38
Viewing the database log	39
Web applications	40
Opening the web application overview	40
System status	42
Viewing system status	42
Stopping and starting the job queue	43
Stopping and starting the DBQueue	43
About us	45
Contacting us	45
Technical support resources	45
Index	46

Operations Support Web Portal

The Operations Support Web Portal helps you to manage and use your web applications. For more information, see the [An overview of the functions](#) on page 6.

Employees that use the Operations Support Web Portal, must be assigned the **Base roles | Operations support** application role.

Members of this application role:

- Monitor handling of Job queue processes.
- Monitor handling of the DBQueue.
- Create passcodes to enable staff to log in to the Password Reset Portal.

An overview of the functions

This section gives you an overview of the different functions available in the Operations Support Web Portal.

With the Operations Support Web Portal, you can:

- Identify problems in your system ([view](#) and [handle](#) failed processes)
- [Manage](#) processes
- [View](#) the synchronization status of target systems
- [Check](#) the status of services
- [Gain](#) an overview of web applications
- Manage the Job queue ([start and stop](#))
- Manage the DBQueue ([start and stop](#))
- [View](#) an object's change history
- [Create](#) passcodes to enable identities to log in to the Password Reset Portal
- [Manage](#) passwords for identities
- [View](#) the database log
- [View](#) unresolved object references
- [View](#) current (and recommended) system values for analyzing and troubleshooting.

The user interface layout

The user interface of the Operations Support Web Portal is divided into several sections:

Top - header

The header shows the current user, the  (**Log off**) button, and the  (**Info**) button.

Top – menu bar

Using the menu bar, you can navigate within the Operations Support Web Portal to:

- Open the home page
- [Monitor and manage](#) processes
- [Display](#) the database log
- [Display](#) unresolved object references
- [Display](#) all web applications
- [Get](#) an overview of the system status, restart and stop the [Job queue](#) and the [DBQueue](#)
- [Display](#) general and important system information

Work area

The work area changes depending on the menu you opened from the menu bar.

Structure of the Operations Support Web Portal

The user interface is composed of the following main sections.

Home

This overview is also divided into the following sections:

Search

You can use the search to:

- [Search](#) by database object
- [Display](#) an object's Job queue and DBQueue tasks

Notifications

In the **Notifications** pane, you can:

- Quickly recognize if and how errors occurred when processing/running [processes](#)
- Quickly recognize if and how many new [log entries](#) there are

Service issues

In the **Service issues** pane, you can:

- Quickly recognize if and how many [Processes](#) failed or contained errors
- Quickly recognize if and how many [Synchronization projects](#) failed or contained errors
- Quickly recognize if and how many [unresolved references](#) objects there are
- Quickly recognize if other errors were found in the system (such as incorrect compilation)

Status reports

In the **Status reports** pane, you can [check](#) the availability of services.

Process menu

You can use the **Processes** menu to [manage and monitor](#) processes.

Synchronization menu

You can use the **System** menu to perform the following actions:

- You can [display](#) information about synchronizing your target systems with the database and [view](#) reports about synchronization runs.
- You can [post-process](#) outstanding objects
- [Show](#) all objects with unresolved references.

System menu

You can use the **System** menu to perform the following actions:

- You can [obtain](#) a quick overview of the state of your system.
- You can [monitor](#) your HTML applications.
- You can [display](#) all information, warnings, and error messages of various components of One Identity Manager.


Logging in and out

You are required to log in before you can start working with Operations Support Web Portal.

To log in

1. In your internet browser, enter the address of the Operations Support Web Portal.
2. On the login page, select the authentication method you would like to use.
3. Enter your user name and password.
4. Click **Connect**.

To log out

1. In the header, click  (**Profile**) > **Log Off**.
2. In the **Log Off** dialog, confirm the prompt with **OK**.

Your logoff was successful.

TIP: Your system may be configured to log you off automatically if you are inactive for a long period of time.

System information

The Operations Support Web Portal keeps certain additional information about your system for diagnostics, analysis, and troubleshooting on the **System information** page. Use this information to collect general information about your system or to quickly identify problems in different categories and, if necessary, initiate prevention measures.

To find out how to display the page, see [Displaying system data](#) on page 11

On the **System information** page, you will see the following categories and recommended values:

TIP: For ease of use, values that have exceeded the recommended limit are highlighted in color. In addition, you can see your actual values and the values recommended by One Identity (in brackets).

- **Configuration:** Information about One Identity Manager (modules, version, and so on)
- **Customer:** Information about the customer
- **DBServer:** Information about the database server
- **Database:** Information about the database



Related topics

- [Displaying system data](#) on page 11

Displaying system data

You can display information about your system at any time.

To display system information

1. In the header, click  **(Help)** > **About**.
2. In the dialog, click the **System information** tab.
3. On the **System information** tab, expand a category by clicking  in front of it.

This displays the values of the selected category.

4. If you use the data outside the Operations Support Web Portal, for example, for analysis, you can:
 - Click **Copy to clipboard**, to copy all your data to the clipboard and paste it somewhere else.
 - Click **Export as CSV**, to export the data to a comma delimited CSV file.

Related topics

- [System information](#) on page 11

Searching

You can use the search function to find objects in the database.

TIP: You must also use the search to create a passcode for an identity.

There are certain rules that make successful searching possible. The following table uses examples to describe these rules.

Table 1: Rules with examples for searching

Example	Description
John Doe	Finds John Doe but not John Donut. Search results must contain all of the separate terms in the query. A logical AND is used.
John OR Doe	Finds Jane Doe and John Donut. Placing OR between the search terms acts as a logical OR operator. The results of this search contain at least one of the two search terms.
John NOT Doe	Finds John but not John Doe. The results of this search do not contain the term that comes after NOT .
J*	Finds John and Joanna. The * functions as a wildcard for any number of characters to complete the term.
Do?	Finds Doe but not Donut. The ? functions as a wildcard for a single character to complete the term.
"John Doe"	Provides results in which the search terms John and Doe follow one another. Results of this search contain the string in quotes as phrase.
John Doe~	Finds Jon Doe and also other similar results. A tilde ~ after the search term indicates that the search should also find similar results. This means that incorrectly spelled terms can be found, as well. You can specify the level of similarity by adding a number between 0 and 1 (with decimal point) after the tilde ~. The higher the number, the more similar the results.

Related topics

- [Running a search](#) on page 14
- [Displaying Job queue and DBQueue tasks](#) on page 17
- [Creating passcodes for identities](#) on page 19

Running a search

You can search for objects at any time.

To run a search

1. In the menu bar, click **Home**.
2. (Optional) In the overview, in the **Search** section, in the **Search in** menu, select the tables you want to search through.
3. In the search field, enter a search term.
4. In the result list below the search field, click the required result.

In the overview, processes in the Job queue associated with the object are displayed on the **Queues** tab under **Jobqueue** and the respective DBQueue tasks under **DBQueue**. You can also view the history of an object as a timeline or table (see [Displaying object histories](#) on page 16). If the object is an identity, you can create a passcode (see [Creating passcodes for identities](#) on page 19) or manage passwords (see [Managing passwords for identities](#) on page 20).

Related topics

- [Searching](#) on page 13
- [Displaying Job queue and DBQueue tasks](#) on page 17
- [Displaying object histories](#) on page 16
- [Creating passcodes for identities](#) on page 19

Object history

The Operations Support Web Portal allows you to display any changes to an object (for example, an identity) in a timeline or table.

To find out how to display the page, see [Displaying object histories](#) on page 16.

You can view the following information in the change history table view.

Table 2: Object history

Column	Description
Modification date	Shows the date of the change.
Change type	Shows the type of change.
Name	Shows the name of the modified object.
Long name	Shows the long name of the modified object.
Type	Shows the type of the modified object.
User	Shows the user that made the change.

TIP: You can use the elements beneath the table to:

- Specify how many entries you want to display per page.
- Navigate to other pages.

Related topics

- [Displaying object histories](#) on page 16
- [Searching](#) on page 13

Displaying object histories

To view the history of an object

1. In the menu bar, click **Home**.
2. (Optional) In the overview, in the **Search** section, in the **Search in** menu, select the tables you want to search through.
3. In the search field, enter the name of the object for which you would like to view its history.
4. In the result list below the search field, click the required result.
5. In the overview, switch to the **History** tab.
6. Perform one of the following tasks:
 - To display the history graphically in a timeline, select **Timeline** in the menu.
 - To display the history in a table, select **Table** in the menu.

Related topics

- [Object history](#) on page 15
- [Searching](#) on page 13
- [Running a search](#) on page 14

Displaying Job queue and DBQueue tasks

Starting from an object, you can display the Job queue and DBQueue.

To display the Job queue and DBQueue tasks

1. In the menu bar, click **Home**.
2. (Optional) In the overview, in the **Search** section, in the **Search in** menu, select the tables you want to search through.
3. In the search field, enter the name of the object for which you would like to view the Job queue and DBQueue tasks.
4. In the result list below the search field, click the required result.

On an overview page, on the **Queues** tab in the **Job queue** pane, you can see the processes in the Job queue that exist for this object. In the **DBQueue** pane, DBQueue tasks associated with the object are displayed.

The following table lists the tasks that can be found for an object.

Table 3: Overview of tasks for an object

Object type	Task
<ul style="list-style-type: none"> • Hierarchical roles • Organizations • Departments • Cost centers • Locations • Business roles • Application roles 	<ul style="list-style-type: none"> • Tasks for the object • Tasks for assignment requests for the object • Tasks for attestation cases for the object

Object type	Task
Employee	<ul style="list-style-type: none"> • Tasks for the identity • Tasks for hierarchical roles of which the identity is a member • Tasks for requests received by the identity • Tasks for requests placed by the identity • Tasks for attestation cases for the identity • Tasks for system entitlements where a user account is assigned to the identity • Tasks for the identity's user accounts <p>Shared and subidentity user accounts also belong to the "Identity user accounts".</p>
User accounts	<ul style="list-style-type: none"> • Tasks for the user account • Tasks for system entitlements to which the user account is assigned • Tasks for attestation cases for the user account
Groups	<ul style="list-style-type: none"> • Task for the system entitlement • Tasks for attestation cases of the system entitlement

Related topics

- [Searching](#) on page 13
- [Running a search](#) on page 14

Creating passcodes for identities

If identities have forgotten their password for logging into the Web Portal and the passwords cannot be reset with the question and answer feature, you can create passcodes for them. With this passcode, identities can log on to the Password Reset Portal once and for a limited time.

To create a passcode for an identity

1. In the menu bar, click **Home**.
2. On the home page, in the **Search** section, select the **Employees** table in the **Search in** menu.
3. Enter the identity's name in the search field.
4. In the result list below the search field, select your desired search result (of type **Person**).
5. In the overview, switch to the **Passcode** or **Passwords** tab respectively.
6. On the **Passcode** or the **Passwords** tab, click **Create passcode**.
The generated passcode and its validity period are displayed in a dialog.
7. Note or copy the code and send it to the identity.

NOTE: If the four-eye principle is active for your system, you will only obtain the first part of the code here. The second half is sent to the identity's manager. The identity must ask the manager for the second half of the passcode.

Related topics

- [Searching](#) on page 13
- [Running a search](#) on page 14

Managing passwords for identities

You can assign new passwords for identities' user accounts.

To issue a new password for an identity

1. In the menu bar, click **Home**.
2. On the home page, in the **Search** section, select the **Employees** table in the **Search in** menu.
3. Enter the identity's name in the search field.
4. In the result list below the search field, select your desired search result (of type **Person**).
5. On the **Object overview** page, switch to the **Passwords** tab.
6. On the **Passwords** tab, click **Set new password** next to the user account you want to give a new password to.
7. In the **Set New Password** pane, in the **New password** field, enter the password that you want to use.
8. In the **Repeat the password** field, enter the password again.
9. Click **Save**.

Related topics

- [Searching](#) on page 13
- [Running a search](#) on page 14

Status reports

Status reports give you a quick overview of your HTML applications and their status.

Related topics

- [Availability check](#) on page 21
- [Check service availability](#) on page 22

Availability check

The **Service availability check** page shows whether your services are available. For example, you should perform an availability check if you suspect that services are not functioning properly (for example, because the server is unavailable).

To find out how to display the page and check availability, see [Check service availability](#) on page 22.

You can view the following information on the **Service availability check** page.

Table 4: Availability check

Column	Description
Server	Shows the name of the server upon which the service runs.
Connection	Shows whether the server is connected.
Last fetch time	Shows the last time the server was called.
URL	Shows the URL used to access the service.
Executing server	Shows the server upon which the service is run.
IP address (IPv4)	Shows the IPv4 address used to access the service.

TIP: You can use the elements beneath the table to:

- Specify how many entries you want to display per page.
- Navigate to other pages.

Related topics

- [Check service availability](#) on page 22

Check service availability

You can check the availability of your services at any time.

To check service availability

1. In the menu bar, click **Home**.
2. On the home page, click **Start** in the **Status reports** section of the **Service availability check** tile.
3. On the **Service availability check** page, click **Check all services**.
4. See the services/server details list.

Related topics

- [Status reports](#) on page 21
- [Availability check](#) on page 21

Manage processes

In the Operations Support Web Portal, you can use the following pages to manage processes at any time:

- [Process overview](#) on page 23
- [Process details](#) on page 24
- [Process steps](#) on page 27
- [Performance](#) on page 28
- [Synchronization](#) on page 29

Process overview

The **Processes** page shows all processes running in the Job queue and allows you to rerun failed processes.

To find out how to display the page, see [Viewing processes and details](#) on page 25 and how to rerun failed processes, see [Handling failed processes](#) on page 26.

You can view the following information on the **Processes** page.

Table 5: Processes

Column	Description
Process name	Shows the name of the process.
Process task	Shows which process task is currently running.
Actions	<p>Actions that you can perform for the process:</p> <ul style="list-style-type: none"> • Retry: Reruns the process. You can rerun processes that have the status Frozen or Overlimit only. <p>NOTE: Processes with the status Frozen or Overlimit are marked with a beetle icon.</p> <ul style="list-style-type: none"> • Details: Shows the details view of a process.

TIP: Use the filter above the table to limit the number of processes displayed.

TIP: You can use the elements beneath the table to:

- Specify how many entries you want to display per page.
- Navigate to other pages.

Related topics

- [Process details](#) on page 24
- [Viewing processes and details](#) on page 25


Process details

On the **Processes** page, you can display detailed information a certain process. Any steps belonging to the process and their dependencies are displayed.

To find out how to display process details, see [Viewing processes and details](#) on page 25.

You can view the following process information.

Table 6: Process details

Column	Description
Process name/- process step	Shows you the name of the process or process step that is currently running.
Created on	Shows when the process started.
Steps completed	Shows how many process steps have already been completed (status Completed).
Progress state	Shows the process status. The following types of status may be shown: <ul style="list-style-type: none">• True: The process is currently running.• False: The process cannot run yet. The process is waiting for another process to end.• Frozen: The process cannot run. An error has occurred.• Overlimit: The process has been running for too long without changing to the status Completed or Frozen.• Completed: The process was successfully completed.• Delete: The process is being deleted (after completing successfully).
 Show message	Shows you the error message of a failed process.

Related topics

- [Manage processes](#) on page 23
- [Viewing processes and details](#) on page 25

Viewing processes and details

To view processes

1. In the menu bar, click **Processes > Processes**.
The **Processes** page is opened, displaying any ongoing processes.
| **TIP:** Use the filter above the table to limit the number of processes displayed.
2. (Optional) To view details of a process, next to the process, click **Details**.
This opens the **Process details** page where the details of the relevant process are displayed (see [Process details](#) on page 24).

Related topics

- [Manage processes](#) on page 23
- [Process details](#) on page 24

Failed processes

The maximum number of times a process can appear in the Job queue can be limited in order to prevent mass modifications.

If the limit is exceeded, the process steps are set to **Overlimit** status and are therefore no longer collected for processing.

Critical process steps that have failed to be processed are given **Frozen** status.

Related topics

- [Displaying failed Job queue processes](#) on page 25
- [Handling failed processes](#) on page 26

Displaying failed Job queue processes

You can display faulty Job queue processes and their details.

To display failed processes

1. In the menu bar, click **Home**.
2. In the overview, under **Service issues** in the **Process issues** tile, click **View**.
The page **Processes with status "Frozen" "<Jobqueue>"** is opened.

Handling failed processes

You can decide how to proceed with failed processes. For example, you can re-run [processes](#) and [process steps](#) that contain errors.

Sometimes a rerun of the failed process step is not desired. This might occur when the action to be carried out by the process has been carried out manually, for example, an expected directory has been manually added in the meantime. Even so, it may just happen that the process should be rerun even though the error has not been fixed, for example, for a rollback of already processed steps. In this case, to continue with the process, the next process step in the success or failure branch can be [handled](#).

IMPORTANT: When you restart a process, all process steps are processed again. All previously handled processes up to the point at which the error occurred are run again. This can lead to data inconsistencies in certain circumstances.

To re-run a failed process

1. In the menu bar, click **Processes > Processes**.
2. In the **Processes** window, next to the process, click **Retry**.

To re-run multiple failed processes

1. In the menu bar, click **Processes > Processes**.
2. In the **Processes** window, enable the check box next to the processes that you would like to rerun.
3. Click **Actions > Retry**.

To re-run a failed process step

1. In the menu bar, click **Home**.
2. In the overview, under **Service issues** in the **Process issues** tile, click **View**.
3. On the **Frozen processes in "<Job queue>"** page, next to the process whose process step you want to repeat, click **Details**.
4. In the **View Process Details** pane, under **More options**, click **Retry the frozen process step**.
5. Click **Apply**.

To run the subsequent process step

1. In the menu bar, click **Home**.
2. In the overview, under **Service issues** in the **Process issues** tile, click **View**.
3. On the **Frozen processes in "{0}" in "<Job queue> "** page, click **Details** next to the process whose process step you want to repeat.
4. In the **View details of a process** pane, under **More options**, click **End with success** or **End with error**.
5. Click **Apply**.

Process steps

The **Process steps** page shows any processes currently in the job queue and the number of process steps that must be run for the process.

To find out how to display process steps, see [Viewing process steps](#) on page 27.

You can view the following information on the **Process steps** page.

Table 7: Process steps

Column	Description
Process name	Shows the name of the process.
Count	Shows the number of process steps contained in the process.

TIP: You can use the elements beneath the table to:

- Specify how many entries you want to display per page.
- Navigate to other pages.

Related topics

- [Manage processes](#) on page 23
- [Viewing process steps](#) on page 27

Viewing process steps

To view process steps

- In the menu bar, click **Processes > Process steps**.
The **Process steps** page opens.

Related topics

- [Manage processes](#) on page 23

Performance

The **Processing performance** page displays information about a Job queue's performance.

To find out how to display the page, see [Viewing performance](#) on page 28

You can view the following information on the **Processing performance** page.

Table 8: Performance

Column	Description
Process task	Shows the name of the process task.
Class	Shows the process component class that the process task belongs to.
Process steps/minute	Shows how many process steps can be handled per minute.

TIP: You can use the elements beneath the table to:

- Specify how many entries you want to display per page.
- Navigate to other pages.

Related topics

- [Manage processes](#) on page 23
- [Viewing performance](#) on page 28

Viewing performance

To view Job queue performance

- In the menu bar, click **Processes > Performance**.
The **Processing performance** page opens.

Related topics

- [Performance](#) on page 28
- [Manage processes](#) on page 23

Synchronization

NOTE: You have to set up synchronization before you can view the synchronization status in the Operations Support Web Portal. For more information, see the *One Identity Manager Configuration Guide* and the *One Identity Manager Target System Synchronization Reference Guide*.

The **Synchronization** page shows you information about synchronizing your target systems with the database.

To find out how to display the synchronization status, see [Viewing synchronization status and log](#) on page 30

You can view the following information on the **Synchronization** page.

Table 9: Synchronization

Column	Description
Display name	Shows the name of the synchronization project.
Description	Shows the description of the synchronization project.
Next synchronization	Shows when the synchronization project will be run the next time.
Errors	Shows how many errors occurred the last time the synchronization project was run.
Affected objects	Shows the objects that had to be changed during synchronization, as they deviated from the database.

TIP: You can use the elements beneath the table to:

- Specify how many entries you want to display per page.
- Navigate to other pages.

Related topics

- [Manage processes](#) on page 23
- [Viewing synchronization status and log](#) on page 30

The synchronization project log

From the **Synchronization** page, you can navigate to the **Synchronization log: <name of synchronization project>** page. This page provides you with detailed information about a specific synchronization project. In addition, you can [display a detailed report](#) of every synchronization run.

To find out how to display synchronization projects, see [Viewing synchronization status and log](#) on page 30.

You can view the following information on the **Synchronization log: <name of synchronization project>** page.

Table 10: Synchronization log

Column	Description
Creation time	Shows when the synchronization project started.
Synchronization workflow	Shows the workflow used for this synchronization project.
Synchronization state	Shows the synchronization project's status.
Start configuration	Shows the name of the start configuration used.

TIP: You can use the elements beneath the table to:

- Specify how many entries you want to display per page.
- Navigate to other pages.

Related topics

- [Synchronization](#) on page 29
- [Viewing synchronization status and log](#) on page 30
- [Displaying a synchronization report](#) on page 31

Viewing synchronization status and log

To view the synchronization status of your target systems

1. In the menu bar, click **Synchronization > Synchronization**.
The **Synchronization** page is opened.

2. (Optional) To view a synchronization project log, next to the synchronization project, click **Details**.

The **Synchronization log: <name of synchronization project>** opens, displaying the log of the relevant synchronization project (see [The synchronization project log](#) on page 30).

Related topics

- [Synchronization](#) on page 29
- [The synchronization project log](#) on page 30

Displaying a synchronization report

To view a detailed report about a synchronization project run-through

1. In the menu bar, click **Synchronization > Synchronization**.
2. On the **Synchronization** page, next to the synchronization project, click **Details**.
3. On the **Synchronization log: <name of synchronization project>** page, next to synchronization run, click **Download report**.

Related topics

- [Synchronization](#) on page 29
- [The synchronization project log](#) on page 30

Post-processing outstanding objects

Objects that are not in the target system are marked as outstanding. This prevents objects being deleted because of an incorrect data situation or an incorrect synchronization configuration.

Outstanding objects

- Cannot be edited
- Are ignored by subsequent synchronizations.
- Are ignored by inheritance calculations

This means, all memberships and assignments remain intact until the outstanding objects have been processed.

On the **Outstanding Objects** page, you can get an overview of outstanding objects, delete these objects in the database or add them back to the target system. Additionally, you can reset the status of these objects so that they are no longer marked as outstanding.

You can view the following information on the **Outstanding Objects** page.

Table 11: Outstanding objects

Column	Description
Display name	Displays the object's name.
Last log entry	Shows you the time of the last entry in the synchronization log.

Detailed information about this topic

- [Displaying outstanding objects](#) on page 33
- [Deleting outstanding objects](#) on page 33
- [Resetting outstanding objects](#) on page 34
- [Adding outstanding objects to the target system](#) on page 34

Displaying outstanding objects

You can display outstanding objects sorted by target system.

To display outstanding objects

1. In the menu bar, click **Synchronization > Outstanding Objects**.
2. On the **Outstanding Objects** page, in the **Target system type** menu, select the type of target system that you want to test for outstanding objects.
3. (Optional) To further restrict the displayed entries to a specific object type, select the appropriate type in the **Object Type** menu.

Deleting outstanding objects

You can delete outstanding objects in the database. This removes the **Outstanding** label from these objects.

To delete an outstanding object in the database

1. In the menu bar, click **Synchronization > Outstanding Objects**.
2. On the **Outstanding Objects** page, in the **Target system type** menu, select the type of target system that you want to test for outstanding objects.
3. (Optional) To further restrict the displayed entries to a specific object type, select the appropriate type in the **Object Type** menu.
4. In the list, select the check box in front of the object you want to delete.
5. Click **Delete**.
6. In the **Delete Object** dialog, confirm the query with **OK**.

NOTE: By default, the selected objects are processed in parallel, which speeds up the action. If an error occurs during processing, the action is stopped and all changes are discarded.

To locate the error, disable bulk processing of the objects, which means the objects are processed sequentially. Failed objects are named in the error message. All changes that were made up until the error occurred are saved.

To disable bulk processing

- Uncheck the **Bulk processing** check box.

Resetting outstanding objects

You can reset the status of outstanding objects so that they are no longer marked as outstanding.

To reset an outstanding object

1. In the menu bar, click **Synchronization > Outstanding Objects**.
2. On the **Outstanding Objects** page, in the **Target system type** menu, select the type of target system that you want to test for outstanding objects.
3. (Optional) To further restrict the displayed entries to a specific object type, select the appropriate type in the **Object Type** menu.
4. In the list, select the check box in front of the object you want to reset.
5. Click **Reset**.
6. In the **Reset Object** dialog, confirm the query with **OK**.

NOTE: By default, the selected objects are processed in parallel, which speeds up the action. If an error occurs during processing, the action is stopped and all changes are discarded.

To locate the error, disable bulk processing of the objects, which means the objects are processed sequentially. Failed objects are named in the error message. All changes that were made up until the error occurred are saved.

To disable bulk processing

- Uncheck the **Bulk processing** check box.

Adding outstanding objects to the target system

You can add outstanding objects back into the target system. This removes the **Outstanding** label from these objects.

Prerequisites:

- The table containing the object can be published.
- The target system connector has write access to the target system.

To add an outstanding object to the target system

1. In the menu bar, click **Synchronization > Outstanding Objects**.
2. On the **Outstanding Objects** page, in the **Target system type** menu, select the type of target system that you want to test for outstanding objects.

3. (Optional) To further restrict the displayed entries to a specific object type, select the appropriate type in the **Object Type** menu.
4. In the list, select the check box in front of the object you want to add to the target system.
5. Click **Add to target system**.
6. In the **Add Object** dialog, confirm the query with **OK**.

NOTE: By default, the selected objects are processed in parallel, which speeds up the action. If an error occurs during processing, the action is stopped and all changes are discarded.

To locate the error, disable bulk processing of the objects, which means the objects are processed sequentially. Failed objects are named in the error message. All changes that were made up until the error occurred are saved.

To disable bulk processing

- Uncheck the **Bulk processing** check box.

Unresolved references

On the **Unresolved references** page, you can view unresolved references at any time. Use this function to quickly identify synchronization issues and to take any action as necessary.

If a reference object does not exist in the One Identity Manager database, the object reference cannot be resolved by synchronizing. Unresolvable object references are written to a data store. This ensures that the references remain intact and are not deleted by target system provisioning.

Example

An Active Directory group has an account manager, which owns a domain not in the current synchronization run. The account manager is not in the One Identity Manager database either.

Synchronization cannot assign an account manager. In order to retain the assignment, the object reference is saved with the account manager's distinguished name in the data store.

During each synchronization, One Identity Manager tries to clean up the data store. If referenced objects in the One Identity Manager database exist, the references can be resolved and the entries are deleted from the data store.

For more information, see the *One Identity Manager Target System Synchronization Reference Guide*.

To find out how to display the page, see [Displaying unresolved references](#) on page 37

You can view the following information on the **Unresolved references** page.

Table 12: Unresolved references

Column	Description
Display name	Shows the name of the property whose value cannot be resolved.
Object	Shows the name of the object containing the reference that cannot be

Column	Description
	resolved.
Synchronization project	Shows the synchronization project in which the unresolved reference occurred.
system	Shows the system in which the unresolved reference appeared.
Data	Shows the value of the property that cannot be resolved.

TIP: You can use the elements beneath the table to:

- Specify how many entries you want to display per page.
- Navigate to other pages.

Related topics

- [Displaying unresolved references](#) on page 37

Displaying unresolved references

You can display unresolved references at any time.

To display unresolved references

- In the menu bar, click **Unresolved references**.
This opens the **Unresolved references** page.

Related topics

- [Unresolved references](#) on page 36

Database log

The **Database log** tab displays any information, warnings, and error messages for different components in One Identity Manager.

To learn how to display the page, see [Viewing the database log](#) on page 39.

You can view the following information on the **Database log** page.

Table 13: Database log

Column	Description
Date	Shows the date that the message appeared.
Program	Shows the name of the components that generated the message.
Message	Shows the message text.
Host	Shows the name of the host on which the event occurred.
Logged in system user	Shows the name of the system user who ran the command.

TIP: You can use the elements beneath the table to:

- Specify how many entries you want to display per page.
- Navigate to other pages.

TIP: Use the filter above the table to limit the number of messages displayed.

Related topics

- [Viewing the database log](#) on page 39

Viewing the database log

To view the database log

- In the menu bar, click **System > Database log**.
The **Database log** page is opens.

Related topics

- [Database log](#) on page 38

Web applications

On the **Web applications** page, you can view running web applications at any time and see the details.

To find out how to display the page, see [Opening the web application overview](#) on page 40

You can view the following information on the **Web applications** page.

Table 14: Web applications

Column	Description
URL	Shows the URL used to access the web application.
Web application	Shows the name of the web application.
Debug	Shows whether (Yes) or not (No) the web application runs in debug mode.
Private	Shows whether (Yes) or not (No) the web application runs in private mode (that means if it is generally accessible).
Auto update level	Shows whether (active) or not (inactive) automatic updates are enabled for the web application.

TIP: You can use the elements beneath the table to:

- Specify how many entries you want to display per page.
- Navigate to other pages.

Related topics

- [Opening the web application overview](#) on page 40

Opening the web application overview

You can open the web application overview at any time.

To open the web application overview

- In the menu, click **System > Web applications**.
The **Web applications** page is opened.

Related topics

- [Web applications](#) on page 40

System status

On the **System status** page, you can view the status of current DBQueues or Job queues at any time. You can also check whether the database is up-to-date or must be recompiled. You can also stop the DBQueue or Job queue, or restart them.

To find out how to display the page, see [Viewing system status](#) on page 42.

On the **System status** page, you can see if:

- The DBQueue is running
- The Job queue is running
- The database is functioning properly
- The database is up-to-date

Related topics

- [Viewing system status](#) on page 42
- [Stopping and starting the job queue](#) on page 43
- [Stopping and starting the DBQueue](#) on page 43

Viewing system status

To display the system status

- In the menu, click **System > System status**.
The **System status** page opens.

Related topics

- [System status](#) on page 42

Stopping and starting the job queue

On the **System status** page, you can stop and restart the Job queue.

In certain situations, you may have to use the One Identity Manager Service to stop processes immediately. For example, changes within One Identity Manager could cause bulk entries to be made into the job queue, resulting in a system overload.

To stop the Job queue

1. In the menu, click **System > System status**.
2. On the **System status** page, in the **Job queue** tile, click **Stop**.
3. In the **Stop job queue** dialog, confirm the prompt with **Yes**.

To restart the Job queue

1. In the menu, click **System > System status**.
2. On the **System status** page, in the **Job queue** tile, click **Start**.
3. In the **Start Job queue** dialog, confirm the prompt with **Yes**.

Related topics

- [System status](#) on page 42
- [Stopping and starting the DBQueue](#) on page 43

Stopping and starting the DBQueue

On the **System status** page, you can stop and restart the DBQueue.

In certain situations, you may have to use the DBQueue Processor to stop processes immediately. For example, changes within One Identity Manager could cause bulk entries to be made in the DBQueue, resulting in a system overload.

To stop the DBQueue

1. In the menu, click **System > System status**.
2. On the **System status** page, in the **DBQueue** tile, click **Stop**.
3. In the **Stop DBQueue** dialog, confirm the prompt by clicking **Yes**.

To restart the DBQueue

1. In the menu, click **System > System status**.
2. On the **System status** page, in the **DBQueue** tile, click **Start**.
3. In the **Start DBQueue** dialog, confirm the prompt by clicking **Yes**.

Related topics

- [System status](#) on page 42
- [Stopping and starting the job queue](#) on page 43

One Identity solutions eliminate the complexities and time-consuming processes often required to govern identities, manage privileged accounts and control access. Our solutions enhance business agility while addressing your IAM challenges with on-premises, cloud and hybrid environments.

Contacting us

For sales and other inquiries, such as licensing, support, and renewals, visit <https://www.oneidentity.com/company/contact-us.aspx>.

Technical support resources

Technical support is available to One Identity customers with a valid maintenance contract and customers who have trial versions. You can access the Support Portal at <https://support.oneidentity.com/>.

The Support Portal provides self-help tools you can use to solve problems quickly and independently, 24 hours a day, 365 days a year. The Support Portal enables you to:

- Submit and manage a Service Request
- View Knowledge Base articles
- Sign up for product notifications
- Download software and technical documentation
- View how-to videos at www.YouTube.com/OneIdentity
- Engage in community discussions
- Chat with support engineers online
- View services to assist you with your product

A

availability check 21

C

change history 15

display 16

component 8

create

passcode 19

D

database 11

database log 38

display 39

DBQueue

start 43

stop 43

DBQueue assignments

display 17

DBServer 11

details

display 25

display

change history 16

DBQueue assignments 17

details 25

failed process 25

frozen process 25

history 16

Job queue task 17

limit 11

performance 28

process details 25

process step 27

processes 25

synchronization report 31

synchronization status 30

system information 11

system status 42

threshold value 11

unresolved references 37

web applications 40

F

frozen 25

functions 6

H

history 15

display 16

I

identity

passcode 19

J

Job queue

start 43

stop 43

- Job queue task
 - display 17
- journal 38
 - display 39

L

- limit 11
 - display 11
- log 38
 - display 39
- log in 10
- log out 10

M

- manage
 - processes 23
- monitor
 - processes 23
 - system status 42
 - web applications 40

O

- object history 15
- open
 - web applications 40
- overview 6
 - processes 23

P

- passcode
 - create 19
- performance 28
 - display 28

- process details 24
 - display 25
- process overview 23
- process step 27
 - display 27
- processes
 - display 25
 - incorrect notification 25
 - manage 23
 - monitor 23
 - overview 23
 - viewing details 25

R

- recommendation 11
- recommended values 11
- run
 - DBQueue 43
 - Job queue 43
 - searching 14

S

- searching 13
 - run 14
- service availability 21
 - verify 22
- show frozen process 25
- status reports 21
- stop
 - DBQueue 43
 - Job queue 43
- structure 7-8
- synchronization 29
 - show report 31

- status display 30
- synchronization log 30
- system 11
- system information 11
 - display 11
- system status
 - display 42
 - monitor 42

T

- target system 29
- threshold value 11
 - display 11

U

- unresolved references 36
 - display 37
- user interface 7

V

- verify
 - service availability 22

W

- web applications 40
 - display 40
 - monitor 40
 - open 40